

# COMPANY PROFILE

PT FISCO STRATEGIC SYNERGY

**WWW.FISCOSS.TECH** 



# WELCOME FROM OUR CEO

# PT FISCO STRATEGIC SYNERGY

Welcome to FISCO GROUP.

We are a business entity committed to supporting the energy and industrial sectors through a wide range of professional services, including:

- Engineering Consultancy & Technical Assessments
- Inspection & Assessment of Surface Equipment in the Oil & Gas Industry Geothermal,
   Mineral & Coal Mining, and Chemical Processing Industries
- Manpower Supply & Outsourcing Services for technical and operational roles
- Occupational Health, Safety, and Environmental (HSE) Inspections
- Maintenance, Repair & Overhaul (MRO) Services for Industrial Equipment
- Safety and Quality Management System Audits (ISO, SMK3, etc.)
- Competency-Based Training and Certification
- Procurement and Supply of Equipment, Chemicals, and Tools

We are committed to driving continuous improvement and innovation in all aspects of our services. Our strategies are designed to anticipate future industry needs, comply with regulatory frameworks, and adapt to evolving social and cultural dynamics.

Headquartered in South Jakarta, with branch offices across several provinces and international locations, we operate in diverse environments that require agility and resilience. We believe our greatest asset is the dedication, professionalism, and technical expertise of our team.

As we continue to grow, we remain focused on attracting and developing top talent to support our vision and deliver measurable value to our clients and partners.

Thank you for your interest in FISCO GROUP.

We look forward to working with you, and we hope to inspire you to be part of our continued journey.

Warm regards,

Fistareni Nirbita
Chief Executive Officer
FISCO GROUP

# WHY US?

# PT FISCO STRATEGIC SYNERGY

### **BECAUSE WE ARE ALWAYS BE**

#### Committed

Have high commitment and enthusiasm to provide satisfaction to Partners and Customers.

#### Professional

We try to provide the best and on time to all our customers and partners

### The Best in Quality Assurance

We always control products and quality according to SOP to maintain the quality of our products

#### Reliable Human Resorces

We have a team and partners who are professional and have experience in their respective fields.

### Competitive Prices

We can adjust your budget and needs according to your wishes and needs

#### • Flexible

We strive to provide convenience for customers and of course with the best service

#### Collaborative

We are ready to collaborate with partners who have the same passion and goals as us especially in order to meet achievement targets reliably and accurately

# OUR VISION & MISSION PT FISCO STRATEGIC SYNERGY

# **VISION:**

Being a leading company in the state and has a High Dedicate Global Innovative in delivering the supply of goods & services as a professional, reliable, secure, and be The Best in the alignment of accuracy, quality, and quantity.

# **MISSION:**

For working implementation, we always provide priority to give and to be:

- The Best Quality
- Trusted
- Guaranteed
- Full of Innovative
- Accurate
- Competitive
- Flexible
- Collaborative

# **WORK EXPERIENCES**

# PT FISCO STRATEGIC SYNERGY

- 1. Design & Redesign Vessel
- 2. Remaining Life Assesment
- 3. Reverse Engineering & RLA Pipeline
- 4. RLA Pipeline
- 5. Penyediaan Jasa Tenaga Bantu Operasional Alat Angkat, Alat Angkut Berat dan Ringan SCM PT. Pertamina EP Asset 3 Jatibarang Field
- 6.Kontrak Jasa Borongan Inspeksi Teknis Peralatan dan Fasilitas Produksi Fungsi Asset 3 Oil & Gas Transportation Periode 24 bulan Kalender
- 7. Penyediaan Jasa Tenaga Kerja Bantu Operasional Fungsi Surface Fasilities Asset 3 PT. Pertamina Asset 3
- 8. Jasa Penelahaan Design
- 9. Jasa Pekerjaan Inspeksi Menara Komunikasi PT. Pertamina Asset 3
- 10. Risk Assessment (RA) & RLA Pipeline
- 11. Reverse Engineering & RLA Peralatan
- 12. RLA Peralatan
- 13. Jasa Konsultasi Analisa Penyesuaian Harga Gas
- 14. Jasa Pembuatan Laporan Risk Assesment 2 Jalur Pipa (Line Pipa KTT 20 & Line Pipa KTT 43)
- 15. Pelaksanaan Support Kebutuhan Item Lifting Equipment
- 16. Pelaksanaan Support Kebutuhan Item HSE Equipment
- 17. Penelaahan Design Engineering "Pembangunan CO2 Removal & DHU di SP Karang Baru Untuk Perbaikan Sales Gas" PT Pertamina Ep Regional 2 Field Jatibarang
- 18. Penelaahan Design Engineering "Pembangunan Jaringan Pipa Penyalur Di Kawasan Industri IMM2100 Cibitung - Bekasi"
- 19. Penelaahan Design Engineering "Pembangunan SPPBE PT. Migas Sahabat Sejati – Deli Serdang, Sumatra Utara"
- 20. Maintenance Provision Repair Services for 3 & 4 Portacamp Petrogas (Basin) Ltd
- 21. Penelaahan Desain Cluster Jalur Interkoneksi Pertamina EP Zona 7
- 22. Penelaahan Desain Jalur Interkoneksi Flowline Pertamina EP Zona 7



# OUR SERVICES

**WWW.FISCOSS.TECH** 



# **OUR SERVICES**

# PT FISCO STRATEGIC SYNERGY

#### 1.ASSESSMENT

- Remaining Life Assessment (RLA)
- Risk Assessment
- Fitness For Service (FFS)
- Risk Base Inspection (RBI)

#### 2.ENGINEERING CONSULTING

- Engineering Design & Calculation
- Reverse Engineering
- Re-Engineering
- Review Design Engineering
- Oil & Gas Production Optimization
- Asset Integrity Management Review & Evaluate

### 3.ENGINEERING PROCUREMENT & CONSTRUCTION (EPC)

#### **4.MANPOWER SUPPLY**

#### 5.TRAINING PROGRAM

# 6.PROCUREMENT & SUPPLY GOODS, SUPPLY CHEMICALS, SUPPLY TOOLS

#### **7.REPAIR & MAINTENANCE**

- Preventive Maintenance
- Corrective Maintenance
- Emergency Maintenance

# 8.MSMS (Mining Safety Management System)

- 9. CONSTRUCTION, ARCHITECTURE & INTERIOR DESIGN
- 10. SAFETY INSPECTION
- 11. FIRE PROTECTION SYSTEM & HYDRANT SYSTEM

# Remaining Life Assessment (RLA)

#### Remaining Life Assessment (RLA)

The remaining life assessment is an attempt to measure, and predict the residual life equipment, the technician can plan the replacement or repair. Effective management of major equipment requires capital-intensive strategic decision-making as the equipment is nearing the end of its useful life anticipated. If the treatment can be done to extend the life of equipment, expenditures may be delayed, have and a positive effect on the company's financial performance.

### We will help you to do the Remaining Life Assessment for:

- Pressure Vessels
- Storage Tanks
- Pipeline And Vertical Pipe
- Pressure Safety Valve
- Rotating (Compressor, Pumps, etc)
- Electrical
- Crane
- Rig
- Platform
- Etc

#### **Benefits of Doing RLA:**

- 1. You become knowledgeable about the remaining life of your equipment, to prevent premature deterioration.
- 2. You can avoid the occurrences of unwanted suddenas the bursting of your equipment due to already working outside the limits having have been unsuitable

#### The Data Required To Perform RLA:

- 1. NDT (Non-Destructive Testing) Report
- 2. Inspection Report
- 3. Thickness Testing Report
- 4. Maintenance Report

# **Risk Assessment**

#### **Risk Assessment**

A systematic process that involves identifying, analyzing, and evaluating potential risks associated with various activities, operations, and projects in the industry. The goal is to manage and mitigate these risks to ensure the safety of personnel, protect the environment, and safeguard assets. Here are key aspects of risk assessment in the oil and gas industry:

#### 1. Hazard Identification:

- Identify potential hazards associated with exploration, drilling, production, transportation, and refining activities.
- Hazards can include well blowouts, fires, explosions, toxic releases, equipment failures, natural disasters, and human errors.

#### 2. Risk Analysis:

- Quantify and qualify the likelihood and consequences of identified hazards.
- Use tools like risk matrices, fault tree analysis, and event tree analysis to assess the overall risk level of specific scenarios.

#### 3. Consequence Assessment:

- Evaluate the potential consequences of an event, including impacts on human health, safety, the environment, and assets.
- Consider both immediate and long-term consequences.

#### 4. Likelihood Assessment:

 Assess the probability of an event occurring, taking into account factors such as historical data, industry standards, and engineering judgment.

#### 5. Risk Evaluation:

- Combine consequence and likelihood assessments to determine the overall risk level.
- Prioritize risks based on severity and likelihood to focus resources on the most significant threats.

#### 6. Risk Mitigation:

- o Develop and implement strategies to reduce or eliminate identified risks.
- Mitigation measures may include engineering controls, safety protocols, emergency response plans, and the use of advanced technologies.

#### 7. Emergency Response Planning:

- Develop comprehensive emergency response plans to address potential incidents.
- Train personnel in emergency procedures and conduct regular drills to ensure preparedness.

#### 8. Regulatory Compliance:

• Ensure compliance with industry regulations, standards, and government requirements related to health, safety, and environmental protection.

#### 9. Continuous Improvement:

- Regularly review and update risk assessments to account for changes in technology, operations, and external factors.
- Learn from incidents and near misses to enhance risk management processes.

#### 10. Stakeholder Communication:

 Communicate risks and risk management measures to stakeholders, including employees, regulatory agencies, and local communities.

# Fitness For Service (FFS)

#### **Fitness For Service (FFS)**

Fitness for Service (FFS) is a best practice and standard used by the oil & gas and chemical process industries for in-service equipment to determine its fitness for continued service. FFS serves as a rational basis for defining flaw acceptance limits and allows engineers to distinguish between acceptable and unacceptable flaws.

Most equipment can continue in service despite small flaws, and to repair or replace equipment that can still be used would be an unnecessary and costly expense. In addition, unnecessary weld repairs can do more harm than good and create unnecessary risks to personnel in many cases.

#### We used the reference of API RP 579-1 / ASME FFS-1

Requires increasing amounts of data, calculations, effort, and cost to arrive at the most accurate outcomes and possible longer equipment remnant life. In addition to calculations, FFS involves the consideration of additional data (e.g. pitting patterns and depths, corrosion morphology or shape and depth, crack depths and lengths, operating conditions, materials properties, etc.).

Inspection information is often critical input to an FFS assessment.

#### We provide FFS For:

- Pipe and pipeline
- Tank
- Pressure Vessel
- Crane
- Pressure Safety Valve
- Rotating
- Electrical
- Etc.

# **Risk Base Inspection (RBI)**

#### Risk·Base Inspection (RBI)

Risk-based inspection is the process of developing a scheme of inspection based on knowledge of the risk offailure. The essential process is a risk analysis. This is the combination of an assessment of the likelihood (probability) of failure due to flaws damage, deterioration, or degradation with an assessment of the consequences of such failure.

#### The information gained from this process is used to identify

- a) The type of damage that may potentially be present
- b) Where such damage could occur
- c) The rate at which such damage might evolve
- d) Where failure would give rise to danger. Areas at high risk usually have credible damage mechanisms combined with high consequences from structural failure, the release of hazardous substances, or stored energy.

A suitable inspection scheme will deploy techniques at a frequency that provides adequate confidence about the condition, taking account of the damage mechanisms and the reliability of the inspection techniques used.

We used references: API Recommended Practice 580 and Base Resource Document 581

# **Engineering Design & Calculation**

#### **Engineering Design & Calculation**

This is the decision-making process (often repeatedly) in which the basic sciences, mathematics, and engineering sciences are applied to convert resources optimally to meet the stated objectives. Among the basic elements of the design process are the establishment of objectives and criteria, synthesis, analysis, construction, testing, and evaluation.

The engineering design process is a multi-step process including research, conceptualization, feasibility assessment, defining the design requirements, preliminary design, detailed design, production planning and design tools, and finally production.

"We will assist you in designing and calculating an industrial equipment of your form: "

# For Chemical Process Industry, Oil and Gas Industry, and the like: Engineering Design & Calculation:

- Piping Stress Analysis
- Flow Calculation
- Pressure Drop
- Back Pressure
- Process Design Calculation
- Pressure Vessel Calculation
- Tank Calculation
- Electrical

And we also can help with the As-Built and Re-drawing of the equipment you are

# Reverse Engineering & Re-Engineering

#### **Reverse Engineering**

Reverse engineering is the process of dismantling a finished product to understand how it works, often with the goal of reconstructing or replicating it without needing the original documentation. Reverse engineering is used when the original design is no longer available, helping to extend the lifespan of outdated systems.

#### It is carried out when there is a need to:

- Identify equipment and the relationships between equipment when documentation is missing for a part.
- Discover how an item was originally made, including studying technology and history that might be lost.

#### **Re-Engineering**

Re-engineering involves improving an existing product by redesigning it to enhance performance, functionality, or efficiency. It is a proactive approach focused on updating or upgrading systems.

#### It is carried out when there is a need to:

- Improve performance and functionality
- Reduce costs and increase efficiency
- Add features to the original design

# **Review Design Engineering**

#### **Review Design Engineering**

The process of evaluating or examining the design engineering aspects of a project, system, or product. This review is conducted to ensure that the design meets specified requirements, standards, and objectives. The aim is to identify any potential issues, improvements, or compliance issues in the design before moving on to the next phases of the project.

The review of design engineering can occur at various stages of a project, including the conceptual design phase, detailed design phase, and even during the construction or manufacturing phase. It may involve interdisciplinary teams, including designers, engineers, quality assurance personnel, and project managers.

The goals of a design engineering review may include:

- Ensuring that the design aligns with the project requirements and specifications.
- Identifying and addressing any potential flaws, errors, or omissions in the design.
- Verifying that the design complies with relevant industry standards and regulations.
- Assessing the feasibility and practicality of the design in terms of construction, operation, and maintenance.

Overall, the "Review Design Engineering" process contributes to the quality assurance and successful implementation of engineering projects by addressing design-related challenges and ensuring that the final product or system meets the intended objectives.

# Oil & & Gas Production Optimization

We help you to perform a Production Optimization Exploitation of Oil and Gas, byanalysis, calculation, and simulation models. Optimization of the production can be:

- 1. Production System Analysis
  - Nodal System Analysis Model
  - Nodal System Analysis Application
- 2. Reservoir Performance
  - Equations and Inflow Performance Relationship
  - Real-Time Performance of Oil Wells
  - Performance Prediction of Oil Wells
  - Real-Time Performance of Gas Wells
  - Performance Prediction of Gas Wells
  - Effect of Water Production
- 3. Pressure Drop of Fluid Flow in Pipes
  - General Equations and Concepts
  - Fluid Properties: Density, Compressibility Factor, etc.
  - Well-Flow Correlations
  - Pipeline Flow Correlations
  - Chokes and Valves Pressure Drop
  - Effect of Velocity
- 4. Total System Analysis
  - Tubing Design
  - Flow line Size
  - Effect of Stimulation
  - Chokes and Valves
  - Effect of Completion
- 5. Artificial Lift Method
  - Gas Lift
  - Submersible Pump
  - Sucker Rod Pump
  - Hydraulic Pump
- 6. Nodal Analysis and Production Optimization
  - Pressure Drop Calculation in Steam Line
  - Pressure Calculation in Injection Wells
  - Pressure Calculation in Production Wells
  - Total Analysis Approach for Production Optimization
  - Production Optimization Application
- 7. EOR Methods

# **Asset Integrity Management Review & Evaluate**

The process of systematically examining and assessing the effectiveness of Asset Integrity Management (AIM) practices within an organization. Asset integrity management involves ensuring that assets (such as equipment, facilities, and infrastructure) operate safely, reliably, and efficiently throughout their lifecycle. The review and evaluation process is essential for identifying strengths, weaknesses, and opportunities for improvement in the organization's asset management strategies.

#### The review process may encompass various aspects:

- Documentation and Procedures: Assessing the adequacy and effectiveness of documented procedures and protocols related to asset integrity.
- Compliance: Ensuring that the organization complies with relevant industry standards, regulations, and best practices in asset integrity management.
- Risk Assessment: Evaluating the effectiveness of risk assessment processes in identifying and addressing potential threats to asset integrity.
- Inspection and Maintenance Practices: Reviewing the methods and frequency of inspections, maintenance activities, and monitoring systems in place to preserve asset integrity.
- Data Management: Assessing how data related to asset conditions, inspections, and maintenance activities are collected, managed, and utilized.
- Performance Monitoring: Evaluating the effectiveness of performance monitoring systems to detect deviations from expected asset performance.
- Training and Competence: Ensuring that personnel involved in asset integrity management are adequately trained and competent.

The goal of the review and evaluation process is to identify areas where improvements can be made to enhance the reliability, safety, and efficiency of the assets. It may involve recommendations for process improvements, the adoption of new technologies, or adjustments to existing practices.

Ultimately, a robust Asset Integrity Management Review & Evaluate process contributes to the overall success and sustainability of an organization's operations by safeguarding its critical assets and infrastructure.

# QUALITY ASSURANCE & QUALITY CONTROL ENGINEERING

#### "WE PROVIDE QA/QC ENGINEER SERVICES"

Our Quality Assurance and Quality Control (QA/QC) services can be rolled out in any sector – electric power and generation, oil and gas, chemical, civil engineering, etc. – and at any stage of a project. Our QA/QC services focus on:

#### **PROJECT QUALITY**

Development of a Project Quality Manual to incorporate procedures and flowcharts. Once established, the manual is extended to encompass second- and third-tier documentation covering all aspects of the operations.

Development of a Project Quality Plan, audit schedule and the appropriate data packages, including advice on their suitability to achieve effective control of the project. Maintenance of a non-conformance register for the project, issuance of non-conformance reports (NCRs) and follow-up on corrective action and closure.

Review of all design activities to ensure conformance with project specifications.

### **PROCUREMENT QUALITY**

Auditing and surveillance activities at the vendor's facilities/works during the manufacturing of equipment or modules to ensure compliance with the required code, standard or project specification.

Adherence to the approved Project Quality Plans is verified and can cover mechanical and electrical packages.

#### **CONSTRUCTION QUALITY**

Provide site surveillance and auditing by specialist engineers and inspectors (both precommissioning, as well as during manufacture, construction and installation) to ensure quality compliance in the areas of construction management, supervision and engineering.

Report on results of inspections, providing recommendations to address any area of non-conformance by the contractor.

# ENGINEERING PROCUREMENT & CONSTRUCTION (EPC)

We provide Engineering, Procurement & Construction in one line and one stop to make synergy from the first step to end step, make it more efficiency and effective to get the best budget with low cost and the best Quality.

# MANPOWER SUPPLY

We provide employee placement services according to the needs of our clients. We are looking for the best candidates for employment, from fresh graduates to experienced workers.

#### The workforce we provide includes:

- Oil and Gas field workforce: Engineers, Inspectors, Operators, and Maintenance Technicians
- Management and Engineering experts
- Professional support services: finance, Marketing, Law, and Administration
- Other supporting staff: Driver, OB, and Cleaning Service

# TRAINING PROGRAM

We provide training programs & certification every month and can be adjusted based on requests from interested participants.

#### **Software Training:**

- INSPECT CODEWARE
- ASN
- AUDIT SMKP
- Engineering Solution
- TKDN MIGAS
- ETC

# PROCUREMENT & SUPPLY GOODS, SUPPLY CHEMICALS, SUPPLY TOOLS

As a leading provider in the realm of procurement and supply, our company excels in delivering an extensive array of services tailored to meet the diverse needs of our clients. With a steadfast commitment to excellence, we specialize in the procurement and supply of goods, chemicals, and tools essential for various industries and sectors. Our comprehensive approach encompasses meticulous vendor selection, rigorous quality control measures, and streamlined logistics to ensure seamless delivery of high-quality products. Whether it's sourcing raw materials for manufacturing, supplying specialty chemicals for research and development, or providing a wide range of tools for various applications, our dedicated team strives to exceed expectations and uphold the highest standards of reliability, efficiency, and customer satisfaction. With our expertise and unwavering dedication, we stand ready to be your trusted partner in procurement and supply, empowering your business to thrive in today's competitive landscape.

# REPAIR & MAINTENANCE

#### **Preventive Maintenance**

Preventive maintenance is an activity of care and precautions taken to prevent damage to your equipment. The equipment will experience the value of depreciation (decrease) when used continuously. Therefore, the need for inspection, assessment, and servicing regularly or periodically. It is also useful to prevent damage - damage to the unexpected and find the conditions or circumstances that may lead to the production facilities being damaged during the production process. So, all the production facilities of the treatment (preventive maintenance) would be guaranteed continuity of work and always worked in conditions or circumstances that are ready to beused for any operations or the production process at any time.

Preventive maintenance that we do between are:

- 1. Painting and Coating
- 2. Corrosion Preventive System

#### **Corrective Maintenance**

Corrective maintenance (CM) is a maintenance activity carried out after the machine or production facilities were damaged or interference that can not function and produce properly.

### **Emergency Maintenance**

Emergency Maintenance (Emergency Care) is performed when the sudden death or the equipment can not be used in a period of unexpected (sudden damage) because of damage or abnormalities that cause such equipment can not be operated. This treatment is not planned and carried out repairs to prevent more serious consequences.

# MSMS (MINING SAFETY MANAGEMENT SYSTEM)

**MSMS** Audit is a systematic and independent examination of the fulfillment of established criteria to measure the results of activities that have been planned and implemented in the implementation of MSMS by the company.

- The Companymakes the Procedure for the Implementation of the MSMS Audit
- Objectives of Internal Audit: Determine Effectiveness and achievement of Vocational School Implementation
- Basis of Audit: Results of Risk Assessmentsand Previous Audit Results

# CONSTRUCTION, ARCHITECTURE & INTERIOR DESIGN

#### **Examples of Architecture Design services we provide are:**

- Design Housing
- Design office
- Design Hotel
- Design School
- Design Fuel (SPBU)
- Design SPBG
- Design Place of Worship
- Design Working Space
- Etc

### **Example of Interior Design services we provide are:**

• Design of interior fixed, mobile, and Decorative temporary

# SAFETY INSPECTION

#### **Function Safety Inspection:**

- Can detect a damage to the equipment before the accident risk was greater (things wear out)
- Can provide feedback (feedback) on whether the equipment is purchased or sufficient trained workers (people are not perfect)
- Can detect the changes/modifications (conditions change) in the operating unit are adequate and do not create new problems
- To increase confidence in the management of tasks and their responsibility to prepare a safe workplace

#### We provide inspections for equipment:

- Pipe and Pipeline
- Tank
- Vessel
- Crane
- Rotating
- Electrical
- Pressure Safety Valve

# FIRE PROTECTION SYSTEM

We can provide and design the fire protection system for your House, Office, Hospital, Public Space, Pabric, Smelter, Refinery, Mining Fields, Oil and Gas Fields

Function of a Fire Protection System from our company

- Early detection: Fire protection systems include detectors that can identify the presence of smoke, heat, or flames early on, allowing for a swift response.
- Alarm activation: Once a potential fire is detected, the system activates alarms to alert occupants, enabling quick evacuation and minimizing potential harm.
- Emergency communication: Integrated systems may facilitate communication with emergency services and provide information to aid in a coordinated and efficient response.
- Evacuation Guidance: Fire protection systems can include features like exit signs and emergency lighting to guide occupants safely out of the building during a fire

# **APAR (ALAT PEMADAM API RINGAN)**






Sprinex is a liquid agent package type automatic fire extinguishing equipment which was devised and developed as lessons from a catastrophic fire occurred at special elderly nursing home in 1987 in Japan.

Integrated control multiple-line fire extinguishing system for building. It can be used at various scene such as; hotels, dormitories, apartments, hospitals, social welfare facilities, kindergartens, schools for disabled students, group homes. Main unit can be installed inside or outside of building. Each system line covers floor area up to 13m2 or 21m2 depending upon extinguishing agent capacity.

### **SPRINEX 3-step automatic fire extinguishing**



**SPRINEX** starts activating only after both of two thermo sensors are activated

### **Advantage of SPRINEX Comparing With Sprinkler System**

- Easier installation & space saving
- Quicker and securer fire detection
- Higher fire extinguishing performance
- Less secondary damage
- Stronger & tougher for accidents
- Easier maintenance


### **SPRINEX TECHNICAL DATA**

## 1) SPRINEX (FSSM500IV)

#### **Specifications**

Authorization number in Japan	PGA-006
Model	FSSM500IV
Туре	Separate controller multiple-line type
Number of sub unit for 1 controller	Max. 3 units
Capacity of fire extinguishing agent	216 L / each sub unit
Max. covering line	50-line/125-line/175-line
Covering floor area	21m²/each line
Number of discarge nozzle in each line	4 pcs or 9 pcs
Agent discharge time	Approx. 140 sec
External electric power	AC100V

Dimension & weight	Туре	Width (mm)	Depth (mm)	Height (mm)	Weight (kg)
	50-line	550	211	960	51
Controller	125-line	550	211	1800	85
	175-line	1065	211	1436	115
Cub unit	Indoor	1050	450	1350	480
Sub unit	Outdoor	1087	560	1454	540




# 2) SPRINEX (FSSM500IV)

#### **Specifications**

opecinication is	
Authorization number in Japan	PGA-006
Model	FSSM500IV
Туре	Incorporated controller multiple-line type
Number of sub unit for 1 main unit	Max. 2 units
Capacity of fire extinguishing agent	216 L / each unit
Max. covering line	50-line
Covering floor area	21m²/each line
Number of discarge nozzle in each line	4 pcs or 9 pcs
Agent discharge time	Approx. 140 sec
External electric power	AC100V

Dimension & weight	Туре	Width (mm)	Depth (mm)	Height (mm)	Weight (kg)
Main unit	Indoor	1050	450	1800	540
Main unit	Outdoor	1087	560	1910	610
Sub unit	Indoor	1050	450	1350	480
Sub unit	Outdoor	1087	560	1454	540



# 3) SPRINEX (FSSM013H)

### Specifications

Authorization number in Japan	PGA-008
Model	FSSM013H
Туре	Independent multiple-line type
Capacity of fire extinguishing agent	108 L
Max. covering line	30-line
Covering floor area	13m²/each line
Number of discarge nozzle in each line	4 pcs
Agent discharge time	Approx. 60 sec
External electric power	AC100V
	-

Dimension & weight	Туре	Width (mm)	Depth (mm)	Height (mm)	Weight (kg)
Unit	Indoor	720	560	2000	350



Unit

# 4) SPRINEX mini

#### Specifications

Authorization number in Japan	PGA-001 PGA-002 PGA-017 PG		PGA-009		
Model	CPW13044	CPW13092	CPW13161B	CPW13094	
Installation (indoor)	Wall mount Closet storage Corner		Corner install	Floor standing	
Туре	Independent stand-alone single-line type				
Capacity of fire extinguishing agent	16 L 18 L 16 L 36 I			36 L	
Covering floor area	13m²				
Number of discarge nozzle	4 pcs				
Agent discharge time	Approx. 18 sec Approx. 28 sec Approx. 31 sec Approx. 28 s			Approx. 28 sec	
External electric power	No need because of self-contained battery				

Dimension	Width	Depth	Height	Weight
& weight	(mm)	(mm)	(mm)	(kg)
CPW13044	900	180	400	43
CPW13092	380	205	830	44
CPW13161B	230	205	1400	42
CPW13094	734	195	830	87



# FIRE HYDRANT SYSTEM

### Fire hydrant systems can be classified into three types, as follow:

- Building Hydrant System
- Field/Yard Hydrant System
- Municipal/ City Hydrant System.

Building Hydrant System: is a extinguishing system installed in buildings by the building owner.

Field/Yard Hydrant System: is a fire extinguishing system that is installed outside the building or in the yard, generally there is a hydrant pillar.

City / Municipal Hydrant System: which is specifically installed by the city government and supplied from PDAM. The fire hydrant system consists of a hydrant pump which functions to channel water from the storage tank to the nozzle.

#### Types of Fire Hydrant System Pumps:

- Jockey pump, this pump is the most commonly used pump for firefighting because this pump distributes hydrant water when in standby position therefore, the water is always in the network.
- Electrical pump is a pump that functions to circulate water in the system with a greater flow rate capability compared to the previous pump. This pump works based on a certain pressure according to needs. This pump works when the water flow requirement is high.
- Diesel Pump, this pump works using diesel as a driving force, therefore, this type of pump is very useful when PLN cuts off electricity.



# OUR PRODUCTS

**WWW.FISCOSS.TECH** 



# **APD**

# **ALAT PELINDUNG DIRI**



**SAFETY SHOES** 



**SAFETY SUIT** 



**SAFETY HELMET** 



**SAFETY MASK** 



**SAFETY GLOVES** 



**EAR PROTECTION** 



**SAFETY GOGGLE** 

# VISTROMAX PREMIUM MESH SCREEN



Vistromax Screen Pro is a premium screen designed to response to have a more robust screen cons for conducting sand control in harsh installation environment such as long, open hole horizontal wells.

The Vistromax Screen comprises of multiple woven metal screen layers wrapped on a base pipe and protected byperforated outer shroud. Although the screenhas a multi metal screen layers and covered by an outer shroud, it is thinner than a standard Pre-Packedscreen with a much higher inflow area, offering less fluid pressure differential across.

# **APPLICATION**

- Open hole and casedhole well completion.
- Long open hole horizontal well completion.
- Able to pass medium range hole deviation angle for installation.

# **BENEFIT**

- Fully customizing filter media micron rating range 60 up to 400 suit to each wells characteristics.
- Protective shroud to ensure mechanical stability and erosion.
- Best in the upper part of a vertical well, in horizontal wells, and in open hole completions.




# **VISTROMAX FEATURE**


- Dutch weave or square weave filtration media, available in S/S 304 or 316.
- Sintered filtration construction for filtration media for design customizing.
- Easy to clean surface filtration media.
- All weldedconstruction.
- Fully customized micron ratings from 60 to 400, to suit application.
- All filtration media ratings fully confirmed and verified by reliable glass bead testing.
- Perforated outer Shroud to provide integrity and protection during installation.


# VISTROMAX CONSTRUCTION

- 1.Base Pipe perforated to supply the required flow rate for the application.
- 2.Inner Drainage Layer forming a solid "stand-off" area between the base pipe and the Filtration Media.
- 3.Filtration Media specific by technical specification.
- 4.Stainless Steel, spiral welded protective Shroud forms the outer most later. This is perforated in order to allow the exact flow rate specified.









BroadCast<sup>™</sup> mesh

Dutch Wave Filtration Square Mesh Filtration

# QA & QC

- Our QA/QC process will ensure that we deliver a product or performed service are set of quality criteria or meets the requirements of the client or customer.
- All of our screen product are complywith ISO 17824: Petroleum and natural gas industries - Down hole equipment - Sand screens

# SPECIFICATION VISTROMAX

Base	Base	Outer	Max.	Max	Max.	Max.	Max.	Max. Flow
Pipe Size	Pipe	Shroud	Tensile	Collapse	Brust	Torque	Flow	Rate-Gas
(inch)	Weight	Diameter	Rating	Pressure	Pressure	Rating	Rate-	(MMSCFD/ft)
(,	(lb/ft)	(inch)	(lbf)	(psi)	(psi)	(lb.ft)	Liquid	(,,
	(10/10)	(iiicii)	(101)	(121)	(121)	(IDIIC)		
4 545	4 70	4 000	44.000	0.475	45.00	0.40	(gpm/ft)	
1.315	1.70	1.800	11,800	8,475	4562	840	63	0.34
1.900	3.65	2.400	16,700	6,575	3421	1,670	85	0.49
			-					
2.375	4.60	2.850	16,685	6,865	2881	1,981	100	0.62
2.875	6.40	3/350	19,678	6,506	2451	2,747	118	0.73
2.070	0110	0,000	15,0,0	0,555	2.01	2,7 17	110	017.0
3.500	9.20	4.000	28,192	6,271	2053	4,699	141	0.87
4 000	11.00	4.500	21 704	4 227	1824	E 0E0	150	0.00
4.000	11.00	4.300	31,784	4,227	1024	5,959	159	0.98
4.500	11.60	5.000	35,375	4,048	1642	7,370	176	1.09
			-			-		
5.000	15.00	5.500	38,966	4,622	1493	8,930	194	1.19
5.500	17.00	6.000	42,558	4,074	1369	10,639	211	1.30
5,550	17100	0.000	12,000	1,0,7	1005	10/003		1100
6.625	24.00	7.100	42,124	3,672	1156	12,462	250	1.54
7.000	26.00	7.500	F2 222	2 440	1005	16.666	264	1.63
7.000	26.00	7.500	53,332	3,449	1095	16,666	264	1.63
7.625	29.70	8.100	48,109	2,168	1013	16,237	285	1.76
				-				——————————————————————————————————————
9.625	40.00	10.100	54,095	1,970	902	25,284	356	2.19

# CASTING VALVES GATE VALVE



Design	API 600, ASME B16.34
Testing	API 598
End Connection	ASME B16.5
Face to Face	ASME B16.10
Size Range	1/2" - 24" (>24" upon request)
Class / Rating	150# - 2500#
Material	Carbon Steel & Stainless Steel
Seats	Metal to Metal (TR01~ TR12)
Firesafe Design	Certified Firesafe Test API 6FA

# **CASTING VALVES**

# **GLOBE VALVE**



Design	API 623, BS 1873
Testing	API 598
End Connection	ASME B16.5
Face to Face	ASME B16.10
Size Range	2" - 24" (>24" upon request)
Class / Rating	150# - 2500#
Material	Carbon Steel & Stainless Steel
Seats	Metal to Metal (TR01~ TR12)
Firesafe Design	Certified Firesafe Test API 6FA


# CASTING VALVES SWING CHECK VALVE





Design	API 6D, BS 1868
Testing	API 6D
End Connection	ASME B16.5
Face to Face	ASME B16.10
Size Range	2" - 24"
Class / Rating	150# - 2500#
Material	Carbon Steel & Stainless Steel
Seats	Metal to Metal (TR01~ TR12)
Firesafe Design	Certified Firesafe Test API 6FD

# FORGED VALVES BALL VALVE



Design	API 6D, BS5351
Testing	API 6D
End Connection	ASME B16.5
Face to Face	ASME B16.10
Size Range	1/2" - 24" (>24" upon request)
Class / Rating	150# - 2500#
Material	Carbon Steel & Stainless Steel
Seats	Soft Seat (PTFE, RPTFE, Devlob, Peek, Nylon)
Firesafe Design	Certified Firesafe Test API 607

# FORGED VALVE FORGED GATE VALVE



Design	API 602
Testing	API 598
End Connection	ASME B16.25, B16.5
Face to Face	ASME B16.10
Size Range	1/2" - 2"
Class / Rating	150# - 2500#

## WELLHEAD & CHRISTMAS TREE

## **CHRISTMAS TREE**



Design	API 6A Ed. 21
Testing	API 6A
Size Range	2 1/16" - 7 1/16"
Class / Rating	3000# - 15000#
PSL	1 - 2
Material Grade	AA, BB, DD, EE
Temp. Rating	K, L, N, P, S, T, U, V, X, Y

## WELLHEAD & CHRISTMAS TREE

## WELLHEAD EQUIPMENT



Design	API 6A Ed. 21
Testing	API 6A
Size Range	7 1/16" – 21 1/4"
Class / Rating	3000# - 15000#
PSL	1 - 2
Material Grade	AA, BB, DD, EE
Temp. Rating	K, L, N, P, S, T, U, V, X, Y

## FORGED FLANGES

## **WELDING NECK FLANGES**



Dimension	ANSI B16.5 & ANSI B16.47 Series A/B
End Connection	RF, RTJ, FF
Size Range	1/2" - 60"
Class / Rating	150# - 2500# (>2500# Upon Request
	- API 6A)
Schedule	Sch. 10, Sch. 40, Sch. Std, Sch. 80, Sch.
	160, Sch. XXS
Material Grade	- Carbon Steel: A105, A350 LF1, LF2
	- Stainless Steel : A182, F304/304L,
	F316/F316L
Surface	Anti-rust oil, Yellow paint, Black paint,
Treatment	Hot dip galvanize, Zinc

## **SLIP ON FLANGE**



Dimension	ANSI B16.5 & ANSI B16.47 Series A/B
End Connection	RF, RTJ, FF
Size Range	1/2" - 60"
Class / Rating	150# - 2500#
Material Grade	- Carbon Steel: A105, A350 LF1, LF2
	- Stainless Steel : A182, F304/304L,
	F316/F316L
Surface	Anti-rust oil, Yellow paint, Black paint,
Treatment	Hot dip galvanize, Zinc

## FORGED FLANGES

## SPECTACLE BLIND FLANGE



Dimension	ANSI B16.48
End Connection	RF, RTJ, FF
Size Range	1/2" – 24 (>24" Upon Request)
Class / Rating	150# - 2500#
Material Grade	- Carbon Steel : A105, A350 LF1, LF2
	- Stainless Steel : A182, F304/304L,
	F316/F316L
Surface	Anti-rust oil, Yellow paint, Black paint,
Treatment	Hot dip galvanize, Zinc

## FORGED FITTINGS

## **OUTLET (OLET)**

Туре	Weldolet, Sockolet, Nipolet, Threadolet
Standard	ASTM A105/ASTM A/SA182 & MSS SP-97
Size	1/2" - 24"

## PLUG / UNION / PIPE NIPPLE

Туре	Hex Head Plug, Bull Plug
Standard	ASTM/ASME A/SA182, A/SA105, A/SA312
Size	1/8" – 4"



#### **PIPES**

### **Carbon Steel Pipes (SMLS)**

#### **Grade:**

- SA/A53 Gr.B
- SA/A106 Gr.B
- API-5L Gr.B
- API-5L X-42
- API-5L X-52
- SA/A333 Gr.6
- A335-P11 (Alloy Steel)

## Stainless Steel Pipes (SMLS & WELD)

#### **Grade:**

- SA/A 304/304L
- SA/A 316/316L
- SA/A 317L
- SA/A 321/H
- S31803 (Duplex)

#### **FITTINGS**

## **Carbon Steel Fitting**

#### **Grade:**

- SA/A 234 WPB
- SA/S 420 WPL6
- SA/A 860 WPHY-52
- SA/S 860 WPHY-65
- SA/A 105N
- SA/A 350 LF2

## Stainless Steel Fittings

#### **Grade:**

- 304/304L
- 316/316L
- S31803 (Duplex)

#### **VALVES**

#### **Stainless & Carbon Steel Valves**

• A351 - CF8 = 304

CF8M = 316

CF3 = 304L

CF3M = 316L

• A216 - WCB & A105

#### OCTG

#### Casing

### Pipe

- Grade H-40, J55, K-55, N-80, L-80
- OD 41/2" 20"

### **Tubing**

#### Pipe

- Grade H-40, J55, K-55, N-80, L-80
- OD 23/8" 41/2"

#### **Accessories**

Pup Joint, Cross Over, Coupling

- Grade H-40, J55, K-55, N-80, L-80
- OD: 41/2" 20"

#### **FLANGES**

## **Carbon Steel Flanges**

#### **Grade:**

- SA/A 105N
- SA/A 350-LF2

## **Stainless Steel Flanges**

#### **Grade:**

- 304/304L
- 316/316L
- A182-F51 (Duplex)

#### **PLATES & LONG PROFILE**

#### Rebar

- Round Bar U24 size 6-32 mm
- Deformed Bar U40 size 10-32 mm

#### **Carbon Steel Plate**

- SS400 / A36
- SM 490 YA

**H-Beam** 

**WF-Beam** 

**Welded Beam** 

**Angle Bar & U-Channel** 

## PRODUCT STANDARD

PIPE	CARBON	FORGED	FORGED	STAINLESS
	STEEL	FLANGE	FITTING	STEEL FITTINGS
	FITTINGS			
✓ API 5L	✓ ASTM A 234	✓ ASTM A 105	✓ ASTM A 105	✓ ASTM A 403
✓ ASTM A53	✓ ASTM A 420	✓ ASTM A 182	✓ ASTM A 182	✓ ANSI B 16.9
✓ ASTM A106	✓ ANSI B 16.9	✓ ASTM A 350 LF2	✓ ASTM A 350	✓ ANSI B 16.25
✓ ASTM A120	✓ ANSI B 16.25	✓ ANSI B 16.5	✓ ANSI B 16.11	✓ ANSI B 16.28
✓ ASTM A333	✓ ANSI B 16.28	✓ ANSI B 16.47-A	✓ MSS SP-97	
✓ ASTM A335		✓ ANSI B 16.47-B	✓ MSS SP-95	
✓ ASTM A312				













DTH, ROTARY AIR AND MUD DRILLING



## DTH, ROTARY AIR AND MUD DRILLING



#### **EFFICIENT IN DRILLING HIGHER ON RETURNS**

THE TH10LM IS HYDRAULICALLY POWERED WATERWELL DRILL DESIGNED FOR AIR FOAM, MUD ROTARY AND DOWN THE HOLE DRILLING. IT CAN BE COMBINED WITH A CHOICE OF CIRCULATION SYSTEM AND DRILL PIPE TO ENABLE DRILLING IN SEMI-CONSOLIDATED, CONSOLIDATED FORMATIONS USING AIR, AIR FOAM, MUD ROTARY OR DHD, DEPENDING UPON THE FORMATION WITH SUITABLE DRILLING ACCESSORIES AND TOOLS.

#### + Simplicity at its best

The TH10LM features a simple, reliable power source and hydraulic system. The diesel deck engine powers the drill hydraulics. The hydraulic rotary top-head drive generates a hefty torque for each class of drill in the range. The simplistic design of the driller's console allows the driller to quickly become familiar with this drilling rig.

We also provide a standard manifold that connects to on-board mud system or an air compressor mounted off board to meet different drilling requirements. The connections are standard 2" hammer joint coupling which are very easy to couple or decouple. This makes it even better for drillers to optimize the drilling operation.

#### + Build to last

At Epiroc we have a rich mining history of designing products for the world's worst environments. This design philosophy is translated to our TH10LM water well drill rig resulting in our customers enjoying decades of operation from our equipment.

#### + Global service and parts support

Buying capital equipment from Epiroc is only the beginning of your great experience with us. With our strong customer centers, distributors & dealers network we can support you from all corners of the world.



Dimensions	Metric	Imperial
Length	8.8 m	28.8 ft
Width	2.4 m 7.8 ft	
Height tower down	4.2 m 13.7ft	
Travel speed	Depends on truck	
Weight	20 to 22 tons	44k to 48k lbs

Note: dimensions and weight is subject to vary depending on the truck selection

## DTH, ROTARY AIR AND MUD DRILLING



## Features and benefits



Long mast, long life feed system - The TH10LM has a robust long mast designed to handle up to 6m (20ft) drill pipes and casing pipes. With a reduced number of pipe joints the TH10LM achieves greater depth in a short time thus increasing drilling efficiency. The lattice tower structure is wide enough to store bigger diameter sheaves of feed system that gives better (D/d) ratio resulting in longer life of the ropes & sheaves. The rotation head slides on the guide bars with guide shoes and replaceable nylon pads that makes it easy to replace and costs less to maintain.



Longevity - A heavy duty machine's life is dependent on the quality of materials, welds performed, assembly procedure and tools that are used to make it. We carry more than 100 years of history of producing robust mining machines and the same is implemented for our water well drills. Rigs produced in our factory have branded components, heavy structures are welded by certified welders and assembled by certified technicians with industries latest assembly procedures and tools.



Modular concept - The TH10LM's modular approach ensures the rig is easily adaptable to change even after the customer has taken delivery of the unit. The rig has a plug-and-play feel to it that means the customer can easily add or remove components as desired. This allows the customer to buy kits even after the rig is purchased. Also, this feature enables to mount the rig on local trucks of customer's choice.



Operator comfort & safety - When drilling in tough conditions, it is important that operators and helpers get maximum safety & comfort to work. Our machines come with a full width steel and anti-skid platforms that gives maximum comfort to the drilling crew, resulting in safe working conditions and efficiency in completing a well faster.



## DTH, ROTARY AIR AND MUD DRILLING



#### Technical specifications

		Metric	Imperial	
Feed system	Pullback	11,338 Kgf	25,000 lbf	
	Pulldown	6,802 Kgf	15,000 lbf	
	High speed up	24.5 m/min	80 ft/min	
	High speed down	35.7 m/min	117 ft/min	
Derrick capacity	Rated	15,000 Kgf	33,609 lbf	
Deck engine	Make, model & type	Deutz, BF6L914 & air cooled		
	Power	121 kW @ 2000rpm	162 hp @ 2,000 rpm	
	Make, model & type	MWM, 6.10TCA & water cooled	·	
	Power	147 kW @ 200 rpm (South American market)	197 hp @ 2,000 rpm	
Rotary head	Torque	760 Kg.m	5,500 ft.lb	
	Rotation speed	0-75 rpm (variable)		
	Spindle	2.7/8 API IF or 2.3/8 API Reg		
	Head travel	7 m	22.9 ft	
Table	-	Can be split opened by removing the pin		
	Table opening	400 mm	15.7 inch	
Levelling	-	Hydraulically operated		
	Number, stroke	Four jacks, stroke 762 mm	Four jacks, stroke 30 inch	
Winch	Main	8,163 Kgf	18k lbf	
	Line speed, rope diameter, spooling capacity	0-50 m/min, 16 mm, 50 m	0-164 ft/min, 5/8 inch 164 ft	
	Auxiliary	1,000 Kgf or 1,814 Kgf	2.2 klbs or 4 klbs	
Rod & casing handling	Drill pipe elevator	3 m or 6m	10 ft or 20ft	
Water injection	Piston pump	45 lpm @ 31 bar	0-12 gpm @ 450 psi	
Mud system	Centrifugal	1,134 lpm @ 10 bar	300 gpm @ 145 psi	
	Piston	568 lpm @ 21 bar	150 gpm @ 304 psi	
	Piston	536 lpm @ 22 bar	142 gpm @ 310 psi	
Lubricator	DHD	0-17.5 bar or 0-24 bar	0-250 psi or 0-350 psi	
Welder	Amperes	300 A	300 A	

<sup>·</sup> Note: For truck selection contact your local customer center, our drill module can be mounted on local trucks.

## Standard scope items


- · Feed system driven by hydraulic feed cylinder and rope
- Sturdy long mast and mainframe
- High torque rotation head with hydraulic motors
- · Four hydraulic operated levelling jacks
- Ergonomically designed driller console
- Bubble level

- Efficient hydraulic system
- Drill pipe elevators
- · Standard tools
- · Maintenance & overhaul tool box
- · High quality lamps for night drilling
- Lifting bail





#### **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**



#### **NEXT-GEN DRILLING POWER**

THE EPIROC DM30 XC IS A CRAWLER MOUNTED, HYDRAULIC TOPHEAD DRIVE, MULTI-PASS ROTARY OR DTH DRILLING RIG FEATURING A 9.1 M (30 FT) DRILL PIPE CHANGE. WITH A STARTER ROD UNDER THE ROTARY HEAD, THE DM30 XC HAS A TOTAL CLEAN DEPTH CAPACITY OF 45.1 M (148 FT), DEPENDENT ON THE DRILL PIPE SIZE.

THE EPIROC DM30 XC IS DESIGNED TO HANDLE 101.6 MM (4 IN) UP TO 159 MM (6 1/4 IN) DRILL PIPE. THE DRILL HAS A WEIGHT ON BIT OF 20,000 KGS (44,000 LBS), AND OFFERS EITHER A LOW OR A HIGH PRESSURE COMPRESSOR, MAKING IT SUITABLE FOR ROTARY OR DTH DRILLING APPLICATIONS.

#### **BUILT FOR THE JOB**

HIGH QUALITY AT AN EXCELLENT VALUE SETS THE DM30 XC APART FROM OTHER DRILLS IN ITS CLASS. THE DRILL IS DESIGNED FOR MINING SO THE STRUCTURAL COMPONENTS WILL HOLD UP TO THE HEAVY DUTY CYCLES REQUIRED IN A MINING DRILL – THE FRAME AND TOWER WELDMENTS ARE DESIGNED TO LAST THE LIFE OF THE MACHINE.

#### **POWERFUL PERFORMANCE**

FOR SINGLE PASS APPLICATIONS THE DM30 XC CAN ACHIEVE A CLEAN HOLE DEPTH OF 28 FT (8.5 M) AND FOR MULTI PASS DEPTH CAN ACHIEVE DEPTHS OF UP TO 148 FT (45.1 M). THE 300 GL (1134 L) FUEL TANK ALLOWS THE RIG TO RUN FOR 16 HOURS BEFORE REFILL

#### **OPTIONS TO FIT YOUR APPLICATION**

THE SMALL FOOTPRINT OF THE DM30 XC MAKES IT EASY TO MANEUVER ON TIGHT BENCHES AND SIMPLE TO TRANSPORT OVER THE ROAD BETWEEN PITS.

A SPACIOUS ONE PIECE FOPS (FALLING OBJECT PROTECTIVE STRUCTURE) RATED CAB WITH ELECTRIC OVER HYDRAULIC CONTROLS THAT ARE COMMON ACROSS THE DM SERIES MAKES IT EASY TO OPERATE, ESPECIALLY FOR DRILLERS WHO HAVE EXPERIENCE IN OTHER DM SERIES MACHINES – THE ERGONOMIC CONTROLS LAYOUT ALLOWS IMMEDIATE SWITCH OVER FROM DRILLING TO TRAMMING MODE, THEREFORE INCREASING PRODUCTIVITY.

THE ELECTRONIC AIR REGULATION SYSTEM (EARS) ALLOWS YOU TO EASILY ADJUST YOUR COMPRESSOR TO SAVE HORSEPOWER AND FUEL CONSUMPTION TO DECREASE TCO.

### **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**



 OPERATOR COMFORT INSULATED, **PRESSURIZED** CAB WITH TINTED GLASS AND 6 WAY ADJUSTABLE SUSPENSION **SEAT ELECTRIC OVER** CONTROLLERS. ALL **HYDRAULIC** OPERATIONAL FUNCTIONS CONTROLLED FROM THE DRILLER'S CONSOLE ERGONOMIC CONTROL LAYOUT (IMPROVES EFFICIENCY). **EXCELLENT VISIBILITY 80 DBA RATING CAB** 

• EASE OF MAINTENANCE

DECK LAYOUT FOR EASY ACCESS TO ALL

MAJOR SERVICEABLE COMPONENTS

AVAILABLE OPTIONS TO FACILITATE

SERVICEABILITY:


- -FAST FLUID FILL
- -TOWER ACCESS WITH FALL RESTRAINT
- -CENTRAL LUBRICATION

ENHANCED SAFETY

- -FLUID SAMPLING PORTS

  CONTACT YOUR LOCAL EPIROC

  REPRESENTATIVE FOR A FULL LIST.
- FOPS CAB
  AIREND SAFETY SHUT-DOWN SYSTEM FOR
  HIGH TEMPERATURE BACK-UP ALARM
  HEAD UP PROPEL INTERLOCK TRAMMING
  INCLINOMETER
  LOCKABLE BATTERY AND STARTER
  ISOLATORS JACKS UP INDICATOR LIGHTS



Structural components stand up to the heavy-duty cycles required of a mining drill. Frame and tower weldments are designed to last for the life of the machine. Main frame is verified by FEA and dynamic strain gauging. Designed for longevity and resilience.

## Service and support

Epiroc offers several types of service agreements to meet your operational requirements and maximize your productivity:

#### Variable-price repairs

Service when you need it.

#### Fixed-price repairs

Service with controlled costs.

#### Equipment audit

Scheduled equipment quality control.

#### Preventive maintenance programs

Peace of mind so you can focus on your core business.

#### FLEXIBILITY FOR THE FUTURE

ADD FLEXIBILITY TO YOUR DM SERIES DRILL RIG WITH EPIROC'S RCS LITE. BUILT ON THE RCS 5 PLATFORM THAT COMES STANDARD ON THE PIT VIPER SERIES, RCS LITE OFFERS A NUMBER OF SAFETY AND INTERLOCK FEATURES. IT ALSO PROVIDES A CONVENIENT FOUNDATION TO ADD MORE FUNCTIONALITY AND TECHNOLOGY OPTIONS IN THE FUTURE WITHOUT A MAJOR REBUILD OF THE MACHINE. IN ADDITION, RCS LITE ALLOWS ALL EPIROC ROTARY DRILLS TO HAVE THE SAME ONBOARD DISPLAY AND SYSTEM FOR CONSISTENT OPERATOR TRAINING **AND** SERVICE. MODULAR SOLUTION THAT DELIVERS EFFICIENCY NOW, ALONG WITH THE OPPORTUNITY TO ENHANCE YOUR EQUIPMENT DOWN THE ROAD AS YOUR MINING REQUIREMENTS GROW.

### **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**






HOME SCREEN: ALL SELECTIONS ARE DONE FROM THE MAIN MENU.



DRILL PLAN: SHOWS THE INTERACTIVE DRILL PLAN.



DRILLING: SHOWS INFORMATION ABOUT PRESSURES AND FLOWS FOR VARIOUS SYSTEMS DURING DRILLING.



USER: SETS THE CONTROL SYSTEM LANGUAGE. LOGS IN USERS TO THE CONTROL SYSTEM AND SHOWS USER INFORMATION.



SETUP AND PROPEL: SHOWS MACHINE CONDITIONS DURING SETUP AND WHILE PROPELLING.



PERFORMANCE: SHOWS STATISTICS ABOUT THE MACHINE AND DRILLING CONSUMABLES.

## Technical specifications

#### Sub structure

#### **Mainframe** 66 kg/m (44.35 lb/ft)

- $\cdot \, \text{Weld fabricated I-beam type using wide flange structural steal beam for both rails and crossbeams} \\$
- Designed by Epiroc, main frame is verified by FEA and strain gauge testing

Leveling jack	
Туре	Hydraulic cylinder
Quantity	3
Jack pad diameter	457 mm (18 in)
Position indication	"Jack up" indicator lights on console or RCS screen
Capacities	
Fuel tank	1134 L (300 gal)
Water tank	795 L (210 gal)
Hydraulic tank	397 L (105 gal)
Undercarriage and propel system	
Make	Epiroc or Caterpillar 320L
Mounting	Oscillating walking beam: 5° each side, total 10°
Total length	4.45 m (175 in)
Ground contact	3.65 m (144 in)
Take-up adjustment	Grease slack adjustment; hydraulic recoil
Rollers	9 lower / 2 upper
Location	Strategically located for load distribution relative to the tower position (vertical or horizontal)
Roller bearings	Sealed for life
Track pads	Type: Triple bar grouser Width: 500 mm (19.69 in) Ground pressure: 89.6 kPa (13 psi)
Drive	Hydrostatic closed loop through planetary speed reducer
Propel motors	Two - Hydraulic, axial piston, fixed displacement rating (each): 120 kW (160 HP)
Propel speed range	0 - 3.22 km/hr (0 - 2.0 mph)

## **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**



## Technical specifications

#### Tower, carousel and drill rod handling

Tower, carousel and drill rod ha	nating			
Tower				
Tower construction	Fully welded four main member with open front ASTM A500; rectangular steel tubing			
Tower raising		Two hydraulic cylinders; live tower (raise and lower with full carousel and rotary head at top of tower)		
Rod support	Hydraulic cylinder clamping and	actuation to center drill rod		
Rated capacity				
Single pass depth	8.5 m (28 ft)			
Maximum hole depth	45.1 m (30 ft)			
Carousel (carousel internal to the tower with	key-lock retention)			
Rod length	9.1 m (30 ft)			
	<ul> <li>Four pieces of 101.6 mm (4 in), 1</li> </ul>	14 mm (4-1/2 in) or 127 mm (5 in) rod diameter		
Capacity	• Two pieces of 140 mm (5-1/2 in	)		
	One piece of 159 mm (6-1/4 in)			
	One worm gearbox and one hydr 127 mm (5 in) rod diameter	raulic cylinder for 101.6 mm (4 in), 114 mm (4-1/2 in) or		
Actuation	Two hydraulic cylinders for 140 m	nm (5-1/2 in) rod diameter		
	One hydraulic cylinder for 159 mr	m (6-1/4 in) rod diameter		
Safety		Drill pipe is held securely in carousel by "key lock design" mechanism  No bump system to prevent damage if carousel not stowed		
Drill rods				
Drill pipe diameter x 9.1 m (30 ft)	Thread	Suggested bit diameter		
102 mm (4 in)	2-7/8 in API	127 mm - 152 mm (5 in - 6 in)		
114 mm (4-1/2 in)	3-1/2 in API	140 mm - 171 mm (5-1/2 in - 6-3/4 in)		
127 mm (5 in)	3-1/2 in API or BECO	171 mm (6-3/4 in)		
140 mm (5-1/2 in)	3-1/2 in BECO	7-7/8 in (200 mm)		
159 mm (6-1/4 in)	4 in BECO	200 mm - 220 mm (7-7/8 in - 8-5/8 in)		
Rotary head	'			
Speed range	Variable 0 – 180 RPM (need to ac	djust controller)		
Torque	Variable 0 - 9,300 Nm (0 - 6,870	) lbf-ft)		
Number of motors	One			
Type of motor	Variable displacement axial pisto	n		
Reduction	15.36 : 1			
Horsepower	120 kW (160 HP)			
Travel length	10.8 m (35 ft 5 in)			
Feed system				
Pulldown capacity	Up to 176.4 kN (40,000 lbf)			
Pullback capacity	0 – 57.3 kN (0 – 13,000 lbf)			
Weight on bit	Variable, 0 – 19,800 kg (0 – 44,000 lbs)			
Mechanism type	Hydraulic cylinder with sheave block and cable			
Number of cables - diameter	Two pulldown, two pullback – 19 mm (3/4 in)			
Number of sheaves - outside diameter	Twelve – 397 mm (15.6 in)			
Feed speed	33.8 m/min (111 ft/min)			

## **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**



## Technical specifications

#### Cab and controls

#### Cab

- Thermally insulated and pressurized
- · Adjustable suspension swivel seat with seat belt
- · Two hinged and lockable doors
- Quiet (tested at 80 dBA)
- · Falling Object Protective Structure (FOPS) certified
- Side-mounted air conditioning (easier to service as no roof access required)
- · Ergonomically designed wrap-around console
- · Windshield wiper on drilling and rear tramming window

Controls	
	All drilling and propelling functions are hydraulically powered with ergonomically grouped controls
Panels	<ul> <li>Drilling function</li> <li>Compressor function</li> <li>Propel, leveling and tower raising function</li> <li>Gauges for system pressure, temperature, etc.</li> <li>Engine start and gauges</li> </ul>

#### Hydraulic system

- · Hydraulic pumps mounted on a single three-hole gearbox driven off the engine through a drive shaft
- · Two variable displacement main pumps for propel, drill feed and rotation functions
- · One double pump for setup, auxiliary functions and cooling fan

#### Power package

Airend		
Tier 4 engine only	29.7 m³/min @ 7.6 bar (1,050 cfm @ 110 psi) 25.5 m³/min @ 24 bar (900 cfm @ 350 psi) 29.7 m³/min @ 24 bar (1,050 cfm @ 350 psi)	
Diesel engine (1,800 RPM)		
CAT C15 – 354 kW (475 HP)  CAT C15 – 403 kW (540 HP)  Cummins QSK15 – 354 kw (475 HP)  Cummins QSK15 – 395 kw (530 HP)		
Diesel engine – Tier 4	Cummins QSX15 – 410 kW (550 HP)	

## MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING




## Technical specifications

#### Dimensions and weight

Operating weight

Estimated weight 70,000 - 78,000 lbs (32 - 35 tonnes)


Operating dimensions (Dimensions for DM30 XC)		
	Description	Dimensions mts (in)
Α	Height - tower up	14.8 (586.2)
В	Distance – cab to decking non drill end	7.8 (310)
С	Length - tower down	14.3 (564.8)
D	Length - undercarriage	4.4 (175.4)
E	Length - jack center to jack center	5.3 (29.7)
F	Height – jack to ground, drill end	0.61 (24.5)
Н	Height - tower down	5.11 (201)
I	Width - track inside to track inside	2.16 (85)
J	Width – jack center to jack center, drill end	3.76 (148)
K	Width - overall	4.71 (185.3)
М	Width - track	19.7 (500)
N	Height - tower off	2.92 (115)
P	Height – to lowest point	0.56 (22.2)
R	Rotary head travel	10.2 (402.4)
S	Cab width	1.67 (65.8)
V	Height – top of cab to ground	3.55 (140)
AA	Height – jack to ground, non drill end	0.62 (24.4)
AB	Height - decking to ground	1.35 (53.2)
AC	Length - DCS decking	7.25 (285.3)
AD	Length - CS decking	6.97 (274.2)
AE	Width - decking	3.45 (136)
AJ	Height - tower bottom to ground	3.31 (130.3)
AK	Distance – frame non drill end to tower end	6.47 (254.8)
AL	Distance - Cab to decking non drill end	9.31 (366.7)
AM	Length - Decking cab side	9.84 (387.3)
AN	Width - Overall	5.18 (204.1)
AP	Height - Overall with folded extension drill table	6.47 (254.8)
	·	-




## MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING



Technical specifications





### **MULTI-PASS ROTARY AND DOWN-THE-HOLE (DTH) DRILLING**



OPTIONAL EQUIPMENT


FOR A COMPREHENSIVE LIST, PLEASE CONTACT YOUR LOCAL EPIROC CUSTOMER CENTER.

- ANGLE DRILL PACKAGE 0-30 DEGREES
- EPIROC DUST COLLECTOR
- WATER INJECTION
- WIGGINS CENTRAL SERVICE
- COLD WEATHER OPTIONS
- CUSHION SPINDLE SUB
- RCS LITE
  - BASIC: DRILL DEPTH, PENETRATION RATE AND AUTO LEVEL.
  - CONNECTED: REAL TIME COMMUNICATION, DATA STORAGE AND TRANSMISSION
  - NAVIGATION: GPS AND MOVING MAP DISPLAY OF PATTERN
- AUTOMATIC LUBE SYSTEM
- TOW HOOKS ON NON-DRILL END
- TOWER ACCESS LADDER
- TOWER FALL RESTRAINT
- MAINTENANCE WALKWAYS
- CAB AND TOWER STROBE LIGHTS






SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102–152 MM (4"–6")



SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102-152 MM (4"-6")





# Trustful performer

Everything about the PowerROC T50 says performance and ease of ownership. Its straightforward design provides you with high performance and reliability.

PowerROC T50 is developed and designed for the demanding applications of limestone and aggregate, as well as mines. Thanks to the new developed rock drill COP 3060, the PowerROC T50 provides high penetration rate. Meanwhile, the

perfectly matched engine in either Tier 3 or Tier 4 provides more tons per liter fuel. which results in high efficiency and productivity, while conforming to your local emission standards.



## Main benefits

Reliability - tough, Epiroc quality

**High performance** – fast penetration rates give more meters per shift

Easy and quick positioning thanks to the extendable boom

## SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102–152 MM (4"–6")



## Excellent driller with striking efficiency

Thanks to its modular design and a high degree of commonality with other Epiroc products, reserve parts are only a phone call away thanks to our global service network.



#### Working faster than you expect

Our rigs are built tough. The PowerROC T50 is designed to operate in environments where productivity, durability, and availability are essential. Its straightforward design and power gives you a workhorse you can depend on year after year.



#### Get it right the first time

Our rock drills are known for their high efficiency and constant hole bottom contact due to the double dampening system. Not only does PowerROC T50 have the powerful COP 3060 rock drill, we've also matched it with an Atlas Copco air compressor that provides sufficient amounts of air to ensure a high quality hole. The PowerROC T50 is also equipped with aluminium feed instead of a steel feed, for much straighter and more consistent holes.



#### + Put holes in the ground and not in your pocket

When it comes to work, the PowerROC T50 is all business and easy to own. Simplified hydraulic and electrical systems ensure easier operation and less downtime. All vital functions are at your fingertips for excellent drilling control. Because we understand that long work shifts can drain an operator's energy and productivity, for added comfort the cabin has great visibility, extra vibration dampers, and is ROPS and FOPS certified.

# A comprehensive service offering

Even the best equipment needs to be serviced regularly to make sure it sustains peak performance. An Epiroc service solution offers peace of mind, maximizing availability and performance throughout the lifetime of your equipment. We focus on safety, productivity and reliability.

By combining genuine parts and an Epiroc service from our certified technicians, we safeguard your productivity – wherever you are.



## SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102–152 MM (4"–6")



### Technical specifications

#### Main components

- Track frames with triple grouser pads, cleaning holes and hydraulic track oscillation and two speed traction
- Tier 3 (Stage IIIA) diesel engine/Tier 4 final (Stage IV) diesel engine, CAT C9/CAT C9.3
- · Screw type air compressor
- · Air-conditioned cabin, ROPS and FOPS certified
- · Extendable boom
- · Motor driven aluminium feed system
- · Carousel type rod handling system
- · Hydraulic rock drill
- · Dust collection system

#### Engine

CAT turbo charged, diesel engine C 9, Tier 3/Stage IIIA	Metric	US
Power rating at 1 800 rpm	261 kW	350 hp
CAT turbo charged, diesel engine C 9.3, Tier 4 final/Stage IV		
Power rating at 1 800 rpm	261 kW	350 hp

#### Feed

	Metric	US
Feed extension	1900 mm	74.8*
Feed rate, max	0.7 m/s	138 ft/min
Feed force, max	50 kN	11 240 lbf
Tractive pull, max	50 kN	11 240 lbf
Total length	9 370 mm	369'
Travel length	5 400 mm	212.6"

#### Compressor

Atlas Copco C146, screw type air com- pressor	Metric	US
Working pressure, max	10.5 bar	152 psi
FAD, at normal working pressure	232 L/s	492 cfm

## Electrical system

Voltage	24 V
Batteries	2 x 12 V. 235 Ah
Alternator	24 V. 95 A
Work lights, front	4 x 70 W
Work lights, rear	2 x 70 W
Work lights, feed	2 x 70 W
Warning lamp and reverse alarm buzzer	

#### Hydraulic system

Hydraulic oil cooler	Metric	US
Max ambient temperature	50°C	122'F

#### Volumes

Hydraulic oil tank	380 [	100 US gal.
Hydraulic system, total	470 l	124 US gal
Compressor oil	55 L	14.7 US gal
Diesel engine oil	321	7.9 US gal
Diesel engine, cooling water	51 l	13.5 US gal.
Diesel engine, fuel tank	500 L	132 US gal
Traction gear	31	0.8 US gal
Lubrication tank (ECL)	71	18 US gal

#### Dust collector

	Metric	US
Filter area	20 m <sup>2</sup>	215 sq.ft
Number of filter elements	20 pcs	20 pcs
Cleaning air pressure, max	8.0 bar	116 psi
Cleaning air consumption	2-4 l/pulse	0.06-0.12 cu.ft/pulse

#### Hole range(recommended)

Type of drilling	Drill steel type	Drilling diameter		Max hole depth		Drill steel length	
Single pass		102-152 mm	4-6	5.08 m	16'8'	4 270/3 660/6 096 mm	14712720
Extension drilling	T51, T-Wiz 60 102-152 mm			35 m	118'	4 270 x 7	14' x 7
						3 660 x 7	12'×7

#### Hydraulic rock drill

Rock drill	Impact power		Hydraulic pressure		Impact rate	Max torque		Weight approx	
000 2050	OP 3060 30 kW 40.2 hp	40.21-	240 bar	3 481 psi	50 Hz	2 770 Nm	2 043 lbf/ft	355 kg 78	783 lb
COP 3060 30 kW	40.2 hp 225 bar	225 bar	3 263 psi	43 Hz	2 //U NM	2 043 lbf/ft	355 KG	783 ID	

## SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102–152 MM (4"–6")





### Technical specifications



#### Transport dimensions

	Metric	US
Height (H1)	3 485 mm	137.2"
Length (L1)	10 900 mm	4291'
Feed height 0-0	9 370 mm	368.9"
Weight		
Tier 3/Stage IIIA	22 200 kg	48 943 lb
Tier 4 final/Stage IV	22 800 kg	50 265 lb





#### Selection of options

#### Carrier

- Hydraulic support leg
- Super rotation system
- Service hand lights inside canopy
- Combined warning sound and warning light, beacon type
- Engine air filter pre-cleaner
- · Compressor air filter pre-cleaner
- · Electric pump for filling hydraulic oil
- · Electric fuel filling pump
- · Fast fuel filling system
- Cold weather kit +5°C to -25 °C, including diesel engine heater and compressor regulation heating kit
- Rock drill lubrication oil collection system

#### Safety Cabin

- · Radio
- Reverse camera with cab mounted monitor

#### Hole measuring systems

- 2D angle indicator
- · 3D angle indicator

#### Lube oil, lube system and water mist system

- Central lubrication system
- Thread greasing device, spray system
- · Artic hydraulic oil, VG 32
- · Tropical hydraulic oil, VG 68
- · Biological hydraulic oil, VG 46
- · Water mist system with water pump and 400l water tank

#### Feed

- Wide feed foot
- RHS for T51 12'/14' SPEEDROD
- RHS for T51 12'/14' with 72 mm coupling
- · RHS for T-Wiz 60 12'/14' SPEEDROD
- RHS for T-Wiz 60 12'/14' with 85 mm coupling
- Sleeve retainer


#### Delivered equipment, not mounted

- Conversion kit T51
- Conversion kit T-Wiz 60


## SURFACE DRILL RIG FOR QUARRYING AND OPEN PIT MINING HOLE DIAMETER: 102–152 MM (4"–6")




## Technical specifications




Horizontal reach (mm)



Toe-hole drilling reach



Vertical reach (mm)



Feed swing angles

4 230 3 320 3 130 2 830 200 560

Vertical reach (mm)





## **NEW FMX420 6X4R (EURO 4)**



## **NEW FMX420 6X4R (EURO 4)**

# VOLVO

#### Volvo Construction Equipment

Wheelbase4	1300 mm
Front Axle Capacity	10000 kg
Rear Axles Capacity	38000 kg
Gross Vehicle Weight	18000 kg

#### CAB

Single day Cab Air Condioning Red Safety Belts Emergency Roof Hatch

#### **ENGINE**

#### VOLVO D13A-420 TURBOCHARGED, INTERCOOLER, EURO-4 EMISSION STANDARD (EU4SCR) BIODIESEL B30 CERTIFIED.

Max Output	
Max Torque	m
Number of Cylinders	6
Displacement12.8 dm	13
Cylinder bore x stroke 131 x 158 m	m
Compression ratio 17.8 :	: 1
Economy rev. band1000 - 1500 rp	m
Volvo Engine Brake+ (EBR-VEB+) with maximum 300 Kw	

Volvo Engine Brake+ (EBR-VEB+) with maximum 300 Kw Braking Power @ 2300 rpm.

#### CLUTCH

Single, push-type clutch with large dry friction disc which offer good durability Disc diameter 430 mm. Pneumatic operated electronically controlled.

#### TRANSMISSION

#### VOLVO ATO2612F

12 Speed electronically controlled splitter and range change gearbox with automated Gear Changing system with Overdrive and one Crawler Gear, fied with a Power Take Off and Oil Cooler as standard. Special heavy duty package (TRAP-HD) concern to reinforce Split Synchronizer, Main Gear Dog Clutches and Counter shaft brake.

Maximum Torque :	
Top Gear	
Number of forward gears	12
Number of reverse gears	4
Forward ratio range	11.73-0.78 : 1
Reverse ratio range	13.73-2.48 :1

#### POWER TAKE-OFF & HYDRAULIC PUMP

High speed Gearbox Driven Power Take-off (Standard)

#### SUSPENSION

#### FRONT SUSPENSION

Type of Suspension ......Parabolic Springs Number of springs ...... 4 2 shock absorbers and front stabilizer

#### REAR AXLE & SUSPENSIONS:

#### RTH3815 combined with RADD-TR3

Tandem Axle with Hub Reducon, consist of two spiral bevel single units. Differenal lock inter axles and inter wheels, Two Shock absorbers and Rear Stabilizer as standard.

Type of Suspension Reinfo	rced T- Ride Boogie
Type of Spring	Parabolic – 4 leaf
Capacity	38 Tons
Final reduction ratio	7.22 : 1

#### BRAKE SYSTEM

#### VOLVO BRAKE-ZV (Drum Brake Z-Cam)

Dual Circuit Full Air Brake System with Automatic Adjustment and Asbestos free liners

Auxiliary Parking Brake fitted as standard.

Parking Brake ...... Manually Operated Parking Brake with Electric Button. Full Pressure Hand Controlled Trailer Brake

ABS (Antilock Braking System) and EBS (Electronic Braking System) fitted as standard.

#### **FUEL TANK**

Right hand fitted Steel Fuel Tank with capacity 315 liters.

#### AD-BLUE TANK (EURO-4 ONLY)

Left hand fitted plastic fuel tank capacity 48 liters.

#### FRAME

Constant frame width of 850 mm behind the cab made of high tensile steel section height of 300 mm flange width 90 mm. Web and flange thickness are 8 mm.

Full inner liner thickness 5 mm installed as standard.

All members are cold riveted.

#### TYRE OPTIONS

325/95R24 Tubeless tire Off Road Pattern

Wheels: 8.5"x 24"

Spare wheel same type as front wheel.

#### STANDARD ACCESSORIES

#### Exterior:

- Air Drier Backup Alarm Exterior Smoke Coloured Front Sun Visor
- Front Close View Mirror One Front Towing Devices
- Steel Headlamp Protection Steel Front Bumper
- Two LED Beacon Lamp
   Two Roof Mounted Single Tone Chrome Air Horn
- Vertical pipe muffler outlet V-Shape day Running Light
- White Front Fog Lamps

#### Interior:

- Audio System Basic Cruise Control
- · Driver seat with regular air suspension and arm rest
- Electrical manually controlled air conditioning Electrical window lift
- Fire Extinguisher 3kg Mechanically adjustable steering wheel
- · Manual door locking · Medium level instrument cluster
- 12" High Resoluon Colour Multi Information Display Instrument Cluster
- Passenger seat RED Safety belt Rubber floor mats
- Standard toolkit with 20T Hydraulic Jack Tachograph
- Telematic Gateway with 4G Modern and WLAN
- Dynafleet / Volvo Connect ready

VOLVO reserves the right to modify design and equipment for improvement without prior notification.

<sup>\*)</sup> accessories shown in the picture in this brochure may not be a part of standard equipment.





## **NEW FMX460 8X4R (EURO 4)**



## **NEW FMX460 8X4R (EURO 4)**

# Fourment

#### Volvo Construction Equipment

Wheelbase	6000 mm (Mining)
Front Axle Capacity	
Rear Axles Capacity	
Gross Vehicle Weight	58000 kg

#### CAB

Single day Cab Air Condioning Red Safety Belts Emergency Roof Hatch.

#### **ENGINE**

#### VOLVO D13A-460 TURBOCHARGED, INTERCOOLER, EURO-4 EMISSION STANDARD (EU4SCR) BIODIESEL B30 CERTIFIED.

#### CLUTCH

Single, push-type clutch with large dry friction disc which offer good durability Disc diameter 430 mm. Pneumatic operated electronically controlled.

#### TRANSMISSION

#### VOLVO ATO 2612

12 Speed electronically controlled splitter and range change gearbox with automated Gear Changing system with Overdrive, fied with a Power Take Off and Oil Cooler as standard. Special heavy duty package (TRAP-HD) concern to reinforce Split Synchronizer, Main Gear Dog Clutches and Counter shaft brake.

Type of Suspension	Parabolic Springs
Number of springs	4 2 shock absorbers and front stabilizer
Final reduction ratio	7.99 : 1

#### REAR AXLE & SUSPENSIONS:

#### RTH3815 combined with RADD-TR3

Tandem Axle with Hub Reducon, consist of two spiral bevel single units. Differenal lock inter axles and inter wheels, Two Shock absorbers and Rear Stabilizer as standard.

#### POWER TAKE-OFF & HYDRAULIC PUMP

High speed Gearbox Driven Power Take-off (Standard)

#### SUSPENSION

FRONT SUSPENSION

#### **BRAKE SYSTEM**

#### VOLVO BRAKE-ZV (Drum Brake Z-Cam)

Dual Circuit Full Air Brake System with Automatic Adjustment and Asbestos free liners

Auxiliary Parking Brake fitted as standard.

Parking Brake ...... Manually Operated Parking Brake with Electric Button Full Pressure Hand Controlled Trailer Brake

ABS (Antilock Braking System) and EBS (Electronic Braking System) fitted as standard.

#### **FUEL TANK**

Right hand fitted Steel Fuel Tank with capacity 315 liters.

#### AD-BLUE TANK (EURO-4 ONLY)

Left hand fitted plastic fuel tank capacity 32 liters.

#### FRAME

Constant frame width of 850 mm behind the cab made of high tensile steel section height of 300 mm flange width 90 mm. Web and flange thickness are 8 mm.

Full inner liner thickness 5 mm installed as standard.

All members are cold riveted.

#### TYRE OPTIONS

325/95R24 Tubeless tire Off Road Pattern

Wheels: 8.5"x 24"

Spare wheel same type as front wheel.

#### STANDARD ACCESSORIES

#### Exterior:

- Air Drier Backup Alarm Exterior Smoke Coloured Front Sun Visor
- Front Close View Mirror One Front Towing Devices
- Steel Headlamp Protection
   Steel Front Bumper
   Two LED Beacon Lamp
- . Two Roof Mounted Single Tone Chrome Air Horn
- Vertical pipe muffler outlet V-Shape day Running Light

#### Interior:

- Audio System Basic Cruise Control
- Driver seat with regular air suspension and arm rest
- Electrical manually controlled air conditioning
- Electrical window lift Fire Extinguisher 3kg
- · Mechanically adjustable steering wheel · Manual door locking
- · Medium level instrument cluster
- 12" High Resoluon Colour Multi Information Display Instrument Cluster
- Passenger seat RED Safety belt Rubber floor mats
- Standard toolkit with 20T Hydraulic Jack Tachograph
- Telematic Gateway with 4G Modem and WLAN
- Dynafleet / Volvo Connect ready


VOLVO reserves the right to modify design and equipment for improvement without prior notification.

<sup>\*)</sup> accessories shown in the picture in this brochure may not be a part of standard equipment.





## EC210D VOLVO EXCAVATORS 20.5-23.8 T 167 HP





## The power to perform

Get the most out of your excavator in any application. The EC210D is equipped with a range of features to ensure a superior performance, shift after shift. Designed with Volvo's extensive experience and expertise, this robust machine delivers ultimate productivity and efficient operation in a wide variety of tasks.

#### Powerful Volvo engine

Experience optimum power with the EC210D's robust Volvo engine. Working together with the machine's proven hydraulics, this engine delivers high torque at low rpm for the ultimate combination of performance and improved fuel efficiency.



#### Enhanced operator performance

Operate in comfort for a more productive work shift. The EC210D is equipped with a spacious and safe operator environment offering enhanced all-around visibility, an adjustable seat and ergonomic controls. The improved cab interior features a new I-ECU monitor that displays a range of information for efficient operation.



#### Excellent controllability

The EC210D features increased hydraulic flow for responsive, accurate control in grading and combined operations. Benefit from smoother and easier movement when traveling and lifting simultaneously as well as better grading quality from the harmonized boom and arm movement.



#### Efficient work mode

For fast cycle times and optimum fuel consumption, the EC210D is equipped with the new G4 work mode. Operators can choose the best mode to suit the task at hand, selecting from I (Idle), F (Fine), G (General), H (Heavy) and P (Power max) mode. Choose the correct mode according to your working conditions for added versatility and increased productivity.





## Volvo versatility

Make sure you are ready to tackle any job. Volvo CE offers a comprehensive range of attachments that let you handle a wide variety of tasks. The EC210D can be fitted with a selection of buckets and breakers that work in harmony with the machine to ensure optimal performance and profitability in any application.

#### Quality Volvo buckets

Volvo offers a range of high quality buckets designed to perform efficiently in a variety of materials. Featuring exceptional design and built-in durability, these buckets are equipped with Volvo teeth to handle the toughest applications.

#### Powerful breakers

The EC210D can be equipped with either a top or side mounted Volvo hydraulic breaker built to break even most demanding materials. With consistent power and high breaking force you'll benefit from maximum impact and durability. Set your Volvo breaker at the right frequency to suit your application needs.



#### Attachment Management System

Pre-set and adjust hydraulic flow from the monitor inside the cab with this password-protected management system, providing storage for up to 20 different attachments for increased versatility. You can choose between one or two pump flow to maximize profits and productivity.



#### Optional auxiliary piping

The Volvo-designed hydraulic breaker / shear piping and quick coupler piping option provides optimum flow to the hydraulic attachments. State-of-the-art auxiliary lines allow the correct flow and pressure for special attachments.



#### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



## Adding value to your business

Being a Volvo customer means having a complete set of services at your fingertips. Volvo can offer you a long-term partnership, protect your revenue and provide a full range of customer solutions using high quality parts, delivered by passionate people. Volvo is committed to increasing the positive return on your investment and maximising uptime.

#### Complete Solutions

Volvo has the right solution for you. So why not let us provide all your needs throughout the whole life cycle of your machine? By listening to your requirements, we can reduce your total cost of ownership and increase your revenue.



#### Genuine Volvo Parts

Our attention to detail is what makes us stand out. This proven concept acts as a solid investment in your machine's future. Parts are extensively tested and approved because every part is vital for uptime and performance. Only by using Genuine Volvo Parts, can you be sure that your machine retains the renowned Volvo quality.



#### Service Network

In order to respond to your needs faster, a Volvo expert is on the way to your job site from one of our Volvo facilities. With our extensive infrastructure of technicians, workshops and dealers, Volvo has a comprehensive network to fully support you using local knowledge and global experience.



#### CareTrack

CareTrack is the state-of-the-art Volvo telematics system that provides access to a wide range of machine monitoring information designed to save time and money. Proactively manage service and maintenance schedules, optimize machine and operator performance and reduce fuel costs with CareTrack.



## **EC210D**

#### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**





standard.

Track shoe

Link pitch

Shoe width, triple grouser

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



# letail

Engine		
The engine, which provide excelle	ent perform	nance is equipped
with four cylinder vertical, electro		
injectors, turbo charger with wast		
water cooled diesel type.		
Engine	Volvo	D5E
Max power at	r/min	2 000
Net, ISO 9249/SAE J1349	kW	115
	hp	156
Gross, ISO 14396/SAE J1995	kW	123
	hp	167
Max torque	Nm	670
at engine speed	r/min	1 600
No. of cylinders		4
Displacement	1	4.7
Bore	mm	108
Stroke	mm	130
Electrical System	11011	100
diagnostic information is displaye		
Voltage	V	24
Batteries	V	2 x 12
Battery capacity	Ah	150
Alternator	V/Ah	
Start motor	V - kW	24 - 5.8
Swing System		
The swing system uses an axial p		
The swing system uses an axial p gearbox for maximum torque. An		
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard.	automatic	holding brake and
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed	automatic r/min	holding brake and 12.3
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque	automatic	holding brake and 12.3
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque Drive	automatic r/min kNm	holding brake and 123 76.7
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque Drive Each track is powered by an auto	r/min kNm matic two	holding brake and 12.3 76.7 speed shift travel
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque Drive Each track is powered by an auto motor. The track brakes are multi	r/min kNm matic two-	holding brake and 123 76.7 speed shift travel
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque Drive Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel mo	r/min kNm matic two- disc, sprin tor, brake a	holding brake and 12.3 76.7 speed shift travel
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque Drive Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel mo- are well protected within the trac	r/min kNm matic two- disc, sprin tor, brake a k frame.	holding brake and 123 76.7 speed shift travel ig-applied and and planetary gears
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque  Drive  Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel mo are well protected within the trac Max. drawbar pull	r/min kNm matic two- disc, sprin tor, brake a k frame. kN	holding brake and 123 76.7 speed shift travel ig-applied and and planetary gears 183
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque  Drive  Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel mo are well protected within the trac Max. drawbar pull Max. travel speed (low)	r/min kNm matic two- disc, sprin tor, brake a k frame. kN km/h	holding brake and 12.5 76.7 speed shift travel ig-applied and and planetary gears 183 3.6
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque  Drive  Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel motor are well protected within the trac Max. drawbar pull Max. travel speed (low) Max. travel speed (high)	r/min kNm matic two- disc, sprin tor, brake a k frame. kN	holding brake and 12.5 76.7 speed shift travel ig-applied and and planetary gears 183 3.6
The swing system uses an axial p gearbox for maximum torque. An anti-rebound valve are standard. Max. slew speed Max. slew torque  Drive  Each track is powered by an auto motor. The track brakes are multi hydraulic released. The travel mo are well protected within the trac Max. drawbar pull Max. travel speed (low)	r/min kNm matic two- disc, sprin tor, brake a k frame. kN km/h	holding brake and 12.5 76.7 speed shift travel ig-applied and and planetary gears 183 3.6

Hydi	raulic	sy:	stem
The	hudra	ulie	souste

simultaneous operations.

em and MCV (main control valve) use intelligent technology to control on-demand flow for high productivity. high-digging capacity and excellent fuel economy.

The summation system, boom, arm and swing priority along with boom and arm regeneration provides optimum performance. The following important functions are included in the system: Summation system: Combines the flow of both hydraulic pumps to ensure quick cycle times and high productivity Boom priority: Gives priority to the boom operation for faster

raising when loading or performing deep excavations. Arm priority: Gives priority to the arm operation for faster cycle times in leveling and for increased bucket filling when digging. Swing priority: Gives priority to swing functions for faster

Regeneration system: Prevents cavitation and provides flow to other movements during simultaneous operations for maximum productivity.

Power boost: All digging and lifting forces are increased. Holding valves: Boom and arm holding valves prevent the digging

equipment from creeping.		
Main pump. 2 x variable di	splacement axia	l piston pumps
Maximum flow	l/min	2 x 212
Pilot pump. Gear pump		
Maximum flow	l/min	1 x 18
Relief value setting pressure		
Implement	MPa	32.4 / 34.3
Travel circuit	MPa	34.3
Slew circuit	MPa	27.9
Pilot circuit	MPa	3.9
Hydraulic Cylinders		
Mono boom		2
Bore x Stroke	ø x mm	125 x 1 235
Arm		1
Bore x Stroke	ø x mm	135 x 1 540
Bucket		1
Bore x Stroke	ø x mm	120 x 1 065
LR Bucket		1
Bore x Stroke	ø x mm	100 x 865
Service Refill		
Fuel tank		375
Hydraulic system, total		300
Hydraulic tank		160
Engine oil		17
Engine coolant		15
Slew reduction unit		8.6
Travel reduction unit		2 x 5.8

### Cab

EC210D

600 / 700 / 800 / 900

 $2 \times 46$ 

190

The Volvo cab features a brand new Volvo styling including a strong cab structure, slim pillars and a large glass area for good visibility, a spacious cab, an ergonomic switch layout, efficient air

ventilation and a pressurized	cao.	
Sound Level		
Sound level in cab according	to ISO 6396	
LpA (standard)	dB(A)	73
LpA (tropical)	dB(A)	73.5
External sound level according	g to ISO 6395 and E	EU Noise
Directive (2000/14/EC)	_	
LwA (standard)	dB(A)	102.5
LwA (tropical)	dB(A)	103.5

mm

mm

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



# **Specifications**

MACHINE WEIGHT Description	Shoe width	Operating weight	Ground pressure	Overall width	Operating weight	Ground pressure	Overall width
Units	mm	kg	kPa	mm	kg	kPa	mm
			n boom, 2.9m et, 3 700kg co			n boom, 2.9m et, 4 200kg c	arm, 0.92m³ / ounterweight
	600	20 670	46.2	2 800	21 170	47.4	2 800
Triple groupes	700	20 830	39.9	2 900	21 330	40.9	2 900
Triple grouser	800	21 260	35.7	3 000	21 600	36.2	3 000
	900	21 960	32.8	3 100	21 870	32.6	3 100
Triple grouser, HD	600	22 920	51.3	2 800	22 130	49.5	2 800
			m boom, 2.9m et, 3 700kg co	arm, 0.92m <sup>3</sup> / ounterweight		n boom, 2.9m et, 4 200kg c	
	500	20 890	52	2 890	21 390	53.2	2 890
	600	21 150	43.8	2 990	21 650	44.9	2 990
Triple grouser	700	21 320	37.9	3 090	21 820	38.8	3 090
	800	21 610	33.6	3 190	22 110	34.4	3 190
	900	21 900	30.3	3 290	22 400	31	3 290
Triple grouser, HD	600	22 180	46	2 990	22 680	47	2 990
Double grouser	700	21 890	38.9	3 090	22 390	39.8	3 090
			8.85m boom, 460kg bucket	, 4 900kg			
			counterweight				
Triple grouser	800	23 290	36.2	3 190			
Triple Bronsei	900	23 570	32.6	3 290			

BUCKET	BUCKET SELECTION GUIDE												
				EC210D EC			EC21	210DL					
			Cutting			5.7m boom		5.7m	boom	5.7m	boom	5.7m boom	
		Capacity	width	Weight	Teeth	h 600mm shoe,		4 200kg		600mm shoe, 3 700kg counterweight		600mm shoe, 4 200kg counterweight	
Bucket type							00kg rweight						
		_				2.5m	2.9m	2.5m	2.9m	2.5m	2.9m	2.5m	2.9m
		m <sup>3</sup>	mm	kg	EA	arm	arm	arm	arm	arm	arm	arm	arm
		0.92	1 145	862	5	C	С	С	C	С	C	С	C
Direct fit Buckets pu	General	0.92	1 145	870	5	C	C	C	C	C	C	С	C
	purpose	1.00	1 210	884	5	С	В	С	С	С	С	С	C
	purpose	1.00	1 210	895	6	C	В	C	C	C	C	C	C

Please consult with your Volvo dealer for the proper match of buckets and attachments to suit the application.

The recommendations are given as a guide only, based on typical operation conditions.

Bucket capacity based on ISO 7451, heaped material with a 1:1 angle of repose.

### Maximum materal density

Maximum materal density

1 200~1 300 kg/m3 Coal, Caliche, Shale

B 1 400-1 600 kg/m<sup>3</sup> Wet earth and clay, Limestone, Sandstone C 1 700~1 800 kg/m<sup>3</sup> Granite, Wet sand, Well blasted rock

D 1 900 kg/m³ ~ Wet mud, Iron ore


X : Not recommended


### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**




# **Specifications**

### DIMENSIONS








Description	Unit	EC2	210D	EC21	ODL	EC210DLR
Boom	m	5.7	5.7	5.7	5.7	8.85
Arm	m	2.5	2.9	2.5	2.9	6.25
A Overall width of upper structure	mm	2 700	2 700	2 700	2 700	2 700
B Overall width	mm	2 800	2 800	2 990	2 800	3 190
C Overall height of cab	mm	2 930	2 930	2 930	2 930	2 930
D Tail swing radius	mm	2 850	2 850	2 850	2 850	2 850
E Overall height of engine hood	mm	2 315	2 315	2 315	2 315	2 3 1 5
F Counterweight clearance*	mm	1 025	1 025	1 025	1 025	1 025
G Tumbler length	mm	3 370	3 370	3 660	3 370	3 660
H Track length	mm	4 160	4 160	4 460	4 160	4 460
I Track gauge	mm	2 200	2 200	2 390	2 200	2 390
J Shoe width	mm	600	600	600	600	800
K Min. ground clearance*	mm	460	460	460	460	460
L Overall length	mm	9 745	9 690	9 745	9 690	12 880
M Overall height of boom	mm	3 080	2 940	3 080	2 940	3 055

<sup>\*</sup> Without shoe grouser






De	scription	Unit	Mono Boom	Long Reach	Description	Unit			Long Reach
Во	om	m	5.7	8.85	Arm	m	2.5	2.9	6.25
Α	Length	mm	5 910	9 060	A Length	mm	3 525	3 910	7 330
В	Height	mm	1 585	1 460	B Height	mm	860	860	945
	Width	mm	670	670	Width	mm	440	440	385
	Weight	ka	2 055	2.510	Weight	ka	1 129	1 130	1 309

Includes cylinder, piping and pin, excludes boom cylinder pin

<sup>\*</sup> Includes bucket cylinder, linkage and pin

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**





escripti)	on		Unit	EC210D/	EC210DL	EC210DLR
oom			m	5.7	5.7	8.85
ırm			m	2.5	2.9	6.25
A Max. d	ligging reach		mm	9 550	9 930	15 800
B Max. d	ligging reach on grour	nd	mm	9 380	9 770	15 700
C Max. d	ligging depth		mm	6 330	6 730	12 100
D Max.di	igging depth (2.44 m	level)	mm	6 100	6 540	12 000
E Max. v	ertical wall digging de	pth	mm	5 620	6 090	11 290
Max. c	utting height		mm	9 220	9 460	13 300
G Max. d	lumping height		mm	6 430	6 650	10 950
H Min. fr	ont swing radius		mm	3 670	3 640	5 200
IGGING	FORCES WITH DIE	RECT FIT BUCKET				
Bucket ra	ıdius		mm	1 470	1 470	1 248
	Normal	SAE J1179	kN	123	123	68
Breakout	Power boost	SAE J1179	kN	130	130	-
orce - oucket	Normal	ISO 6015	kN	136	136	77
200101	Power boost	ISO 6015	kN	144	144	-
Tearout	Normal	SAE J1179	kN	112	96	44
orce -	Power boost	SAE J1179	kN	118	102	-
dipper	Normal	ISO 6015	kN	115	99	45
arm	Power boost	ISO 6015	kN	122	105	-
Rotation a	angle, bucket		٥	175	175	178

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**

### Volvo Construction Equipment

# **Specifications**

### LIFTING CAPACITY EC210D

Lifting capacity at the arm end without bucket.

For lifting capacity including bucket, simply subtract actual weight of the direct fit bucket or the bucket with quick coupler from the following values.

1 of many capacity in	Lifting hook		5m		Om		5m		0m		5m		Max. reach	
	related to ground level	Along UC	Across UC	m										
	7.5 m kg											15 280	4 930	5.6
	6.0 m kg							°5 120	4 440			15 200	3 500	6.9
Boom: 5.7m	4.5 m kg					'6 520	*6 520	'5 600	4 270	4 560	2 950	4 460	2 880	7.6
	3.0 m kg					.8 380	6 1 1 0	6 320	4 020	4 460	2 860	4 040	2 570	8.0
Am : 2.5m	1.5 m kg					9 430	5 620	6 060	3 780	4 340	2 750	3.890	2 460	8.1
Shoe: 600mm	0 m kg					9 170	5 400	5 880	3 630	4 260	2 670	3 980	2 500	7.9
CWT: 3 700kg	-1.5 m kg			10 270	10 270	9 130	5 370	5 830	3 580			4 370	2.730	7.4
	-3.0 m kg			*13 680	10 550	9 250	5 470	5 9 1 0	3 660			5 330	3 330	6.5
	-4.5 m kg			*10 530	10.530	°7 520	5.760					'6 610	5 040	5.0
	7.5 m kg							*4 790	4 500			*4 630	4 260	6.2
	6.0 m kg							*4 700	4 500			*4 310	3 160	7.3
Boom: 5.7m	4.5 m kg							5 230	4 320	4 600	2 980	4 110	2 640	8.0
Am : 2.9m	3.0 m kg					'7 810	6 220	16 080	4 050	4 480	2 870	3 740	2 380	8.4
	1.5 m kg					9 500	5 680	6 080	3 800	4 340	2 740	3 610	2 270	8.5
Shoe: 600mm	0 m kg			'5 110	'5 110	9 160	5 380	5 870	3 610	4 230	2 640	3 680	2 300	8.3
CWT: 3 700kg	-1.5 m kg	5 910	'5 910	"9 760	19 760	9 070	5 310	5 780	3 530	4 200	2 610	3 990	2 490	7.8
	-3.0 m kg	10.760	*10 760	*14 440	10 360	9 150	5 370	5 820	3 570			4 750	2 960	6.9
	-4.5 m kg			*11.710	10.760	"8 320	5 600					6 350	4 170	5.6
	7.5 m kg											'5 280	5 240	5.6
	6.0 m kg							'5 120	4 720			5 200	3 750	6.9
Boom: 5.7m	4.5 m kg					16 520	*6 520	°5 600	4 560	4 830	3 170	4 730	3 100	7.6
Arm: 2.5m	3.0 m kg					18 380	6 530	6 410	4 310	4 730	3 080	4 290	2 780	8.0
	1.5 m kg					9 980	6 040	6 420	4 070	4 610	2 960	4 130	2 660	8.1
Shoe: 600mm	0 m kg					9 720	5 810	6 260	3 920	4 530	2 890	4 230	2 700	7.9
CWT: 4 200kg	-1.5 m kg			10 270	10 270	9 690	5 780	6 190	3 870			4 650	2 960	7.4
	-3.0 m kg			13 680	11 320	'9 790	5 890	6 280	3 940			5 660	3 590	6.5
	-4.5 m kg			*10 530	110 530	*7 520	6 180					16 610	5 400	5.0
	7.5 m kg							*4 790	4 790			*4 630	4 540	6.2
	6.0 m kg							*4 700	'4 700			'4 310	3 390	7.3
Boom: 5.7m	4.5 m kg							°5 230	4 610	4 870	3 200	*4 260	2 840	8.0
Am : 2.9m	3.0 m kg					"7 810	6 640	"6 080	4 350	4 750	3 080	3 980	2 570	8.4
	1.5 m kg					'9 570	6 090	6 440	4 080	4 610	2 960	3 840	2 460	8.5
Shoe: 600mm	0 m kg			*5 110	*5 110	9 720	5 800	6 230	3 900	4 500	2 860	3 920	2 490	8.3
CWT: 4 200kg	-1.5 m kg	5 910	*5 910	'9 760	19 760	9 620	5 720	6 150	3 820	4 470	2 830	4 250	2 700	7.8
	-3.0 m kg	"10.760		14 440	11 120	9 700	5 790	6 190	3 860			5 050	3 200	6.9
1	-4.5 m kg			11 710	11 520	*8 320	6 020					*6 350	4 480	5.6

Notes: 1. Machine in "Fine Mode-F" (Power Boost) for lifting capacities. 2. The above loads are in compliance with SAE J1097 and ISO 10567 Hydraulic Excavator Lifting Capacity Standards. 3. Rated loads do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. 4. Rated loads marked with an asterisk (\*) are limited by hydraulic capacity rather than tipping load.

### LIFTING CAPACITY EC210DL

Lifting capacity at the arm end without bucket.

For lifting capacity including bucket, simply subtract actual weight of the direct fit bucket or the bucket with quick coupler from the following values.

Lifting hook 1.5m 3.0m 4.5m 6.0m 7.5m

	Lifting hook	1.	5m	3.4	0m	4.	5m	6.	0m	7.	5m	1	Max. reach	
	related to ground level	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	m
	7.5 m kg											'5 280	*5 280	5.6
	6.0 m kg							*5 120	4 920			*5 200	3 900	6.9
Boom: 5.7m	4.5 m kg					*6 520	*6 520	*5 600	4 750	5 160	3 290	5 050	3 220	7.6
Arm: 2.5m	3.0 m kg					'8 380	6 870	'6 410	4 500	5 060	3 200	4 580	2 890	8.0
Shoe: 600mm	1.5 m kg					*10 010	6 360	6 920	4 250	4 940	3 090	4 420	2 760	8.1
	0 m kg					10 690	6 130	6 760	4 100	4 850	3 010	4 530	2 820	7.9
CWT: 3 700kg	-1.5 m kg			10 270	10 270	10 650	6 100	6 690	4 050			4 980	3 080	7.4
	-3.0 m kg			*13 680	12 220	19 790	6 210	6 780	4 120			6 090	3 750	6.5
	-4.5 m kg			10 530	10 530	'7 520	6510					'6 610	5 670	5.0 6.2
	7.5 m kg							'4 790	'4 790			'4 630	'4 630	6.2
	6.0 m kg							*4 700	*4 700	44.000	0.000	'4 310	3 520	7.3
Boom: 5.7m	4.5 m kg					17.010	6.000	*5 230	4 800	'4 930	3 320	*4 260	2 980	8.0
Arm: 2.9m	3.0 m kg					'7 810	6 980	'6 080	4 530	5 080	3 210	4 240	2 670	8.4
Shoe: 600mm	1.5 m kg			4C 4 4 A	4E 446	19 570	6 420	6 950	4 270	4 930	3 080	4 100	2 560	8.5
CWT: 3 700kg	0 m kg		15.010	*6 110	*5 110	10 550	6 120	6 730	4 080	4 830	2 980	4 190	2 600	8.3
O111.0700mg	-1.5 m kg	'5 910	5 910	19 760	9 760	10 590	6 040	6 640	4 000	4 790	2 950	4 550	2 810	7.8
	-3.0 m kg	*10.760	10 760	*14 440 *11 710	12 010	*10 070 *8 320	6 110	6 690	4 040			5 420 6 350	3 340 4 690	6.9 5.6
	-4.5 m kg			111719	*11 710	0 020	0 300					'5 280	'5 280	5.6
								'5 120	*5 120			'5 200	4 150	6.9
D	6.0 m kg 4.5 m kg					*6 520	*6 520	*6 600	5 050	15 270	3 520	16 280	3 440	7.6
Boom: 5.7m	3.0 m kg					*8 380	7 310	*6 410	4 800	5 350	3 430	4 840	3 100	8.0
Arm: 2.5m	1.5 m kg					10 010	6 800	'7 240	4 550	5 220	3 310	4 680	2 970	8.1
Shoe: 600mm	0 m kg					10 730	6 570	7 130	4 400	5 140	3 240	4 800	3 030	7.9
CWT: 4 200kg	-1.5 m kg			10.270	*10 270	*10 650	6 540	7 080	4 350			5 270	3 3 2 0	7.4
-	-3.0 m kg			13 680	13 040	'9 790	6 650	7 170	4 420			6 440	4 020	6.5
	-4.5 m kg			*10 530	*10 530	17 520	6 950					'6 610	6 060	5.0
	7.5 m kg							*4 790	<b>'4</b> 790			'4 630	*4 630	6.2
	6.0 m kg							'4 700	'4 700			'4 310	3 750	7,3
Boom: 5.7m	4.5 m kg							'5 230	5 100	'4 930	3 550	'4 260	3 170	8.0
	3.0 m kg					'7 810	7 430	*6 080	4 830	15 300		'4 370	2 870	8.4
Arm: 2.9m	1.5 m kg					19 570	6 860	*6 970	4 570	5 220	3 310	4 350	2.760	8.5
Shoe: 600mm	0 m kg			'5 110	°5 110	"10 550	6 560	7 120	4 380	5 1 1 0	3 210	4 440	2 800	8.3
CWT: 4 200kg	-1.5 m kg		*5 910	19 760	*9 760	*10 690	6 480	7 030	4 300	5 080	3 180	4 830	3 030	7.8
	-3.0 m kg		10 760	14 440	12 840	*10 070	6 550	7 080	4 340			5 740	3 590	6.9
	-4.5 m kg			11 710	°11 710	*8 320	6 790					'6 350	5 020	5.6

Notes: 1. Machine in "Fine Mode-F" (Power Boost) for lifting capacities. 2. The above loads are in compliance with SAE J1097 and ISO 10567 Hydraulic Excavator Lifting Capacity Standards. 3. Rated loads do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. 4. Rated loads marked with an asterisk (\*) are limited by hydraulic capacity rather than tipping load.

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



### LIFTING CAPACITY EC210DLR

Lifting capacity at the arm end without bucket.

For lifting capacity including bucket, simply subtract actual weight of the direct fit bucket or the bucket with quick coupler from the following values.

Lifting ho related t		1.5	5m	3.0	)m	4.5	5m	6.0	Om	7.5	5m
ground		Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC
3.0 m k	9					'4 080	"4 080	'2 920	*2 920	"2 320	'2 320
1.5 m k	9					*5 180	*5 180	*3 520	*3 520	*2 680	*2 680
0 m k	9			"1 710	1 710	*4 080	'4 080	*4 000	'4 000	'3 010	3 000
-1.5 m k	9	*1 840	°1 840	*2 380	*2 380	*4 090	*4 090	°4 310	3 780	*3 250	2 800
-3.0 m k	9	*2 530	*2 530	'3 120	'3120	*4 610	'4 610	*4 480	3 650	*3 400	2 680
-4.5 m k	9	*3 260	*3 260	*3 930	*3 930	*5 410	<b>'</b> 5 410	°4 470	3 620	*3 450	2 630
-6.0 m k	9	'4 040	"4 040	*4 830	'4 830	"5 820	5 680	*4 340	3 660	"3 390	2 640
-7.5 m k	9	'4 880	"4 880	<b>'</b> 5 850	'5 850	'5 320	'5 320	'4 030	3 770	"3 180	2 710
-9.0 m k	9			*6350	<b>18 350</b>	*4 560	*4 560	*3 510	*3 510	"2 760	*2 760
-10.5 m l	eg.					*3 380	*3 360	*2 600	*2 600	*1 930	*1 930

Boom: 8.85m Arm: 6.25m Shoe: 800mm CWT: 4 900kg

-7.5 m	kg	'4 880	*4 880	°5 850	"5 850	5 320	*5 320	'4 030	3 770	"3 180	2 710	
-9.0 m	kg			*6350	<b>'6</b> 350	*4 560	*4 560	*3 510	*3 510	*2 760	*2 760	
-10.5 n	n kg					*3 360	*3 360	*2 600	*2 600	*1 930	*1 930	
	hook ed to	9.	Om	10.	5m	12	.0m	13	Om Max		Max. reach	
gro	und vel	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	Along UC	Across UC	m
12.0 m										1510	*510	10.3
10.5 m	ı kg									'450	*450	11.6
9.0 m	kg					*940	'940			'420	*420	12.6
7.5 m	kg			*1 330	1 330	*1 310	*1 310			'410	*410	13.4
6.0 m	kg			*1 430	1 430	*1 370	*1 370	*850	*850	'400	*400	13.9
4.5 m	kg	1 720	"1 720	1 560	1 560	*1 450	*1 450	°1 210	"1 210	'410	*410	14.3
3.0 m	kg	*1 950	"1 950	1 720	*1 720	"1 560	1560	*1450	1 290	'430	*430	14.5
1.5 m	kg	*2 200	*2 200	*1 880	*1 880	*1 670	1 550	*1 520	1 230	'460	*460	14.6
0 m	kg	*2 420	2 320	*2 040	1 830	*1 780	1 460	*1 590	1 170	*510	*510	14.4
-1.5 m	kg	"2 600	2 170	'2 170	1 730	"1 870	1 390	"1 600	1 130	'580	*580	14.2
-3.0 m	kg	"2 720	2 080	'2 260	1 650	"1 920	1 350	"1 100	"1 100	'670	'670	13.7
-4.5 m	kg	*2 770	2 030	*2 290	1 620	*1 930	1 330			*810	*810	13.1
-6.0 m	kg	"2 730	2 030	"2 240	1 630	"1 650	1 360			1 020	"1 020	12.3
-7.5 m	kg	"2 550	2 090	2 050	1 700					"1 370	"1 370	11.2
-9.0 m		*2 160	12 160							*1 890	*1 890	9.7
-10.5 n	n kg									"1 860	1 860	7.6

Notes: 1. Machine in "Fine Mode-F" (Power Boost) for lifting capacities. 2. The above loads are in compliance with SAE J1097 and ISO 10567 Hydraulic Excavator Lifting Capacity Standards.

3. Rated loads do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. 4. Rated loads marked with an asterisk (\*) are limited by hydraulic capacity rather than tipping load.

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



# **Equipment**

STANDARD EQ	UII	PM	ENT
-------------	-----	----	-----

Engine

Turbocharged, 4 stroke diesel engine with water cooling, direct injection and charged air cooler

Air filter with indicator

Air intake heater

Cyclone pre-cleaner

Fuel filter and water separator

Extra water separator

Alternator, 80 A

Electric/Electronic control system

Contronics

Advanced mode control system

Self-diagnostic system

Machine status indication

Engine speed sensing power control

Automatic idling system

One-touch power boost

Power max mode (P)

Safety stop/start function

Adjustable LCD color monitor

Master electrical disconnect switch

Engine restart prevention circuit

High capacity halogen lights:

Frame-mounted 2

Boom-mounted 1

Batteries, 2 x 12 V / 150 Ah

Start motor, 24 V / 5.5 kW

Hydraulic system

Automatic sensing hydraulic system

Summation system

Boom priority

Arm priority

Swing priority

Boom and arm regeneration valves

ECO mode fuel saving technology

Swing anti-rebound valves

Boom and arm holding valves

Multi-stage filtering system

Cylinder cushioning

Cylinder contamination seals

Automatic two-speed travel motors

Hydraulic oil, ISO VG 68

Superstructure

Counterweight: 3 700kg

Access way with handrail

Tool storage area

Punched metal anti-slip plates

Undercovers

Rear view mirror on counterweight

Cab and interior

Cab with roof hatch

Control lock out lever

Travel pedals and hand levers

Adjustable operator seat and joystick control console

Semi-long control joysticks

Heater & air conditioner, manual

Flexible antenna

Radio with USB input

Cab, all-weather sound suppressed, includes:

Cup holders

Door locks

Tinted glass

Floor mat

Horn

Large storage area

Pull-up type front window

Removable lower windshield

Seat belt

Safety glass

Windshield wiper with intermittent feature

Master key

Undercarriage

Undercover

Hydraulic track adjusters

Greased and sealed track link

Track guard

600 mm with triple grousers

Digging equipment

Boom: 5.7 m mono

Arm: 2.9 m

Linkage

Service

Tool kit, daily maintenance

Spare parts kit

### **VOLVO EXCAVATORS 20.5-23.8 T 167 HP**



### OPTIONAL EQUIPMENT

Engine

Rain cap or Oil bath pre-cleaner

Block heater: 240 V

Water separator with heater

Fuel filler pump: 35 l/min or 50 l/min with auto stop

Electric

Extra work lights:

Boom-mounted 1

Cab-mounted 3

Counterweight-mounted 1

Travel alarm

Anti-theft with code lock system

Rotating warning beacon

Hydraulic system

Boom hose rupture valve (HRV) with overload warning device

Hydraulic piping:

Breaker & shear, 1 or 2 pump flow

Quick coupler piping

Additional return filter for breaker and shear

Hydraulic oil, ISO VG 32, 46

Hydraulic oil, longlife oil 32, 46, 68

Cab and interior

Heater & air conditioner, automatic

Electric pedal for breaker and shear

Control joysticks (4 switches, 3 switch & proportional)

Cab-mounted falling object guard (FOG)

Cab-mounted falling object protective structure (FOPS)

Sun screens, front, roof, rear

Rain shield

Rear view camera

Ashtray and lighter

Safety net for front window

Specific key

Superstructure

Counterweight: 4 200kg, 4 900kg

Undercarriage

Full track guard

500 / 600 / 700 / 800 / 900 mm with triple grousers

600 mm HD with triple grousers

700 mm with double grousers

Digging equipment

Arm: 2.5m, 6.25m long reach

Boom: 8.85 m long reach

Linkage with lifting eye

Service

Tool kit, full scale

### SELECTION OF VOLVO OPTIONAL EQUIPMENT

### Rear view camera



Fuel Filler Pump



Oilbath pre-cleaner




Boom & arm configuration




FOPS



Full trackguard









igus® is a specialist in the area of polymer research, with 46 years of experience. Specially designed high performance polymers permit the use of igus e.chains® in almost any area. Humidity, dirt, debris, heat, cold - we have a solution for every environment and our e.chain® materials are metal-free. In more and more heavy-duty areas steel systems are successfully replaced by igus® polymer e.chains®, due to their extra-ordinary capabilities.

- In steelworks
- In the production of building materials
- For composting facilities
- For waste incineration facilities, etc.
- In offshore sectors
- For crane systems In power plants

TÜV certified

In Offshorebereichen

In Kraftwerksbereichen

Bei Krananlagen

TÜV-geprüft

Light weight with high stability

- You provide us with the requirements and we realize them: Corrosion free
- Cost-effective modular design Long life with low maintenance
- Resistance against dirt, chemicals and high or low temperatures
- Proven, tested materials with igus® system guarantee

These are only some of the aspects which we incorporate into the design of your heavy-duty system. Look on the following pages and see what is possible with igus® - plastics for longer life®, in your heavy-duty area.

igus® ist Spezialist im Bereich der Kunststoffforschung und blickt dabei auf 46 Jahre Erfahrung zurück. Besonders entwickelte Hochleistungskunststoffe ermöglichen den Einsatz von igus® e.ketten® in nahezu allen Bereichen. Feuchtigkeit, Schmutz, Späne, Hitze, Kälte - für jede Anforderung haben wir die Lösung und verzichten bei unseren e.ketten®-Werkstoffen völlig auf Stahl und andere Metalle.

In immer mehr Heavy-Duty-Bereichen werden Stahlsysteme aufgrund der außergewöhnlichen Eignung erfolgreich durch igus® Kunststoff e.ketten® ersetzt.

- In Stahlwerken
- Bei der Baustoffherstellung
- Bei Kompostierungsanlagen
- Bei Müllverbrennungsanlagen usw.

Sie geben uns die Anforderungen, wir erfüllen sie:

- Korrosionsfrei
- Geringes Gewicht, bei hoher Stabilität
- Kostengünstiger modularer Aufbau
- Langlebigkeit bei geringstem Wartungsaufwand
- Beständigkeit gegen Schmutz, Chemikalien und hohe Temperaturen
- Bewährter, getesteter Werkstoff mit igus®-Systemgarantie

Das sind nur einige Punkte, die wir bei der Auswahl und Auslegung Ihres "Heavy-Duty-System"berücksichtigen. Überzeugen Sie sich auf den nächsten Seiten selbst davon, was alles mit igus® - plastics for longer life® in Ihrem Heavy-Duty-Bereich möglich ist.



Very demanding industry due to brick dust in the environment. Höchste Beanspruchung durch Ziegelstaub in der Baustoffindust!

### Wienerberger AG, Germany

Handling brickwork Industry: 5050.40.200.0 e.chain®: Travel length: 20 m Speed: 1 m/s Acceleration: 1 m/s<sup>2</sup> Fill weight: ca. 7 kg/m

Highly abrasive brick dust. Plant now in operation for about 5 years, filled with, among other services, igus® CF9 cable Temp. up to + 50°C, approx. 200,000 operational hours/year

#### Wienerberger AG, Deutschland

Branche: Handling im Ziegelwerk 5050.40.200.0 e.kette®: 20 m Verfahrweg: Geschwindigkeit: 1 m/s Beschleunigung: 1 m/s<sup>2</sup> ca. 7 kg/m

Starke Verunreinigung durchabrasive Ziegelstäube, Anlage seit ca. 5 Jahren im Einsatz, befüllt u.a. mit CF9, Temperaturen bis + 50°C, ca. 200.000 Doppelhübe/Jahr

# Road constructions Straßenbau



Very high contamination with construction materials Stärkste Verschmutzung durch Straßenbaumaterialien





### Sambo Heavy Ind., Korea

Road building Industry: 2x 48.075.100.0 e.chain®: Travel length: 14 m Speed: 1 m/s Acceleration: 1 m/s<sup>2</sup> 0.8 kg/m Fill weight:

An asphalt finisher applies hot and cold bitumen mixtures. The e.chain® supplies the front part of the vehicle and is exposed to extreme dirt accumulation.

### Sambo Heavy Ind., Korea

Straßenbau Branche: \* 2x 48.075.100.0 e.kette®: • Verfahrweg: 14 m Geschwindigkeit: 1 m/s Beschleunigung: 1 m/s<sup>2</sup> Befüllung: 0,8 kg/m

Ein Asphaltfinisher bringt heiße und kalte Bitumenmischungen auf. Die e.kette® versorgt den vorderen Fahrzeugbereich und ist stärksten Verschmutzungen ausgesetzt.

# High additional loads Schwere Befüllungen



High additional load due to high numbers of hoses and cables Hohe Zusatzlasten durch Schläuche und Kabel

### ALD, Germany

Industry: Vacuum-Heat treatment 600.35/640.26/640.21/600.32.500.0.LT.LV e.chain®:

18.8 m Travel length: 16m/min Speed: Acceleration: 1 m/s<sup>2</sup> ca. 60 kg/m Fill weight:

e.chain® guides the supply cables of a quenching chamber, which feeds the attached vacuum oven.

### ALD, Deutschland

Befüllung:

Branche: Vakuum-Wärmebehandlung 600.35/640.26/640.21/600.32.500.0.LT e.kette®: Verfahrweg: 18,8 m Geschwindigkeit: 16m/min Beschleunigung: 1 m/s<sup>2</sup>

ca. 60 kg/m \*

Führt die Versorgungsleitungen einer Abschreckkammer die verkettete Vakuumöfen anfährt.





# **Power Plants** Kraftwerke



High reliability despite extreme contamination Sichere Funktion trotz stärkster Verschmutzungen







### KW Mannheim / MVV Mannheim

Industry: Waste cranes 5050R.40.250.S10.0 e.chain®: Travel length: 93.5 m 1.5 m/s 0.5 m/s<sup>2</sup> Acceleration: 12.2 kg/m

Extremely abrasive debris. Twin opposed e.chainsystem® inside the waste-fed power plant, supplying power etc. to the cranes.

#### KW Mannheim / MVV Mannheim

Mülkrane 5050R.40.250.S10.0 e.kette\*: Verfahrweg: Geschwindigkeit: 1,5 m/s Beachleunigung: 0,5 m/s<sup>2</sup> 12,2 kg/m

Starker, abresiver Schmutz. Gegenläufige Anlage im Mülkraftwerk, Versorgung der Krane auf der Kranfahrt.

# Refuse incineration plants Müllverbrennungsanlagen



High reliability in refuse incineration plant Sicherer Einsatz in Müllverbrennungsanlage

#### AVN Dürnrohr Waste incineration facility, Austria

Industry: Waste crane 5050R.35.350.S10.0.E (Crane drive) e.chain®: 5050R.27.350.S10.0.E (Trolley drive) Crane: 52 m, Trolley: 21.5 m Travel length: Crane: 1.33 m/s, Trolley: 1.33 m/s Speed: Acceleration:

Crane: 14.9 kg/m, Trolley: 14.1 kg/m Fill weight:

Extreme accumulation of debris. Crane system in a waste

incineration plant.

#### AVN Dürnrohr Müllverbrennungsanlage, Österreich

Branche:

5050R.35.350.S10.0.E (Kranfahrt) e.kette<sup>a</sup>: 5050R.27.350.S10.0.E (Katzfahrt)

Kran: 52 m, Katze: 21,5 m Verfahrweg: Geschwindigkeit: Kran: 1,33 m/s, Katze: 1,33 m/s

Beschleunigung: 1 m/s<sup>2</sup> Kran: 14,9 kg/m, Katze: 14,1 kg/m

Extreme Verschmutzung. Krananlage in einer Müllver-

brennungsanlage.



# Tunnelbau



Tunnel drilling machine supplied by iguse e.chainse Gesicherter Einsatz der Tunnelbohrmaschine mit Hilfe von igus<sup>o</sup> e.ketten<sup>o</sup>

# Steel mills Walzwerke



Long travel application in very high temperature environment Lange Verfahrwege in direkter Ofennähe

### Herrenknecht, Germany

Tunnel building Industry: e.chain\*: 840.30.450.0 Travel length: 14 m slow Speed: Acceleration: slow around 8.5 kg/m Fill weight:

Tunnel drilling in sections with the aid of an igus®

e.chainsystem<sup>e</sup> which guides all of the hose lines.

### Herrenknecht, Deutschland

Branche: Tunnelbaumschine 840.30.450.0 e.kette\*: Verfahrweg: Geschwindigkeit: langsam Beschleunigung: langsam ca. 8,5 kg/m

Tunnelbohrung in definierten Abschnitten mit Hilfe eines igus» e.kettensystems», das die notwendigen Schlauchleitungen Abschnitt für Abschnitt führt.

### voestalpine Grobblech GmbH, Austria

Industry: Steel Industry e.chaine: 4040CR Travel length: 99 m 2.16 m/s Speed: Acceleration: 0.36 m/s<sup>2</sup> Fill weight: 5.92 kg/m

In the pit furnaces, 4-metre steel slabs are heated in temperatures up to 1,200 °C. Surrounding equipment exposed to heat and flame.

### voestalpine Grobblech GmbH, Österreich

Stahlindustrie Branche: 4040CR e.kette<sup>a</sup>: Verfahrweg: 99 m Geschwindigkeit: 2,16 m/s Beschleunigung: 0,36 m/s<sup>2</sup> 5,92 kg/m Befüllung:

In Tieföfen werden 4-Meter-Brammen erwärmt. Temperaturen bis 1.200 °C oder aus dem Ofen schlagende Flammen stellen hohe Anforderungen an die Anlage.










# Coal-burning Power Plants Offshore Industry Kohle-Kraftwerke



Supply of the bucket-wheel reclaimers using igus® e.chains® Versorgung des Bucket-Wheel-Reclaimers mit igus<sup>o</sup> e.ketten<sup>o</sup>



### Gaozi Kohle-Kraftwerk, China

Industry: Coal-burning power plant rol e.chain® 4040CR.20.350.0 e.chain®:

ca. 180 m Travel length: Speed: 0.5 m/s Acceleration: 0.023 m/s<sup>2</sup> Fill weight: 9.4 kg/m

Two mine coal facilities that to supply the power plant, without any problems for over 1.5 years.

Gaozi Kohle-Kraftwerk, China

Branche: .Kohlekraftwerk Rollen e.kette® "e.kette": 4040CR:20.350.0 ca. 180 m Verfahrweg: Geschwindigkeit: 0,5 m/s Beschleunigung: .0,023 m/s2 Befullung: . 9,4,kg/m

Zwei Anlagen fördern seit 1,5 Jahren problemlos Kohle für den Kraftwerksbetrieb.

# Offshore Industrie



High additional loads in challenging offshore environments Hohe Befüllungsgrade im anspruchsvollen Offshore-Bereich

#### Horizontal Trolley, National Oilwell Varco AS, Norway

Industry: Offshore e.chain\*: 601.20/20/50.500 Travel length: 12,00 m Speed: 1 m/s Acceleration: 3 m/s<sup>2</sup> 50 kg/m , Fill weight:

e.chain<sup>e</sup> with centre-strap design for high stability. High pressure hydraulic hoses + power cables. Extreme weether environment but this chain delivers and delivers. ...

Horizontal Trolley, National Oilwell Varoe AS, Norwegen

e.kette\*: ,601.20/20/50.500 Verfahrweg: 12.00 m Geschwindigkeit! 1 m/s

e.kette<sup>a</sup> mit Mittellaschen für große.Stabilität, satz von Hochdruck-Hydraulikschläuchen und leitungen. Unter extremen Wetterbedingung




# Offshore Industry Offshore Industrie



Pipehandling application supplied by iguse e.chaine Rohrhandlinganlage versorgt mit igus<sup>®</sup> e.kette<sup>®</sup>

# Ship unloaders Schiffentlader



Completely harnessed system on a ship unloader Konfektioniertes System an einem Schiffsentlader

#### Horizontal Trolley for National Oilwell Varco AS, Norway

Fill weight:

Offshore 4040.37.200 e.chain\*: 12.80 m Travel length: 2 m/s Speed: Acceleration: 3 m/s<sup>3</sup>

e.chain® ensures high stability and reliability in pipehandling.

16 kg/m

Horizontal Trolley for National Oilwell Varco AS, Norwegen

Branche: Offshore e.kette\*: 4040.37.200 Geschwindigkeit: 2 m/s Beschleunigung: 3 m/s<sup>a</sup>

Diese e.kette<sup>®</sup> garantiert eine hohe Stabilität und Zuverlässigkeit im Umgang mit Rohren.

### EMO Schiffentlader, Holland

Crane construction Industry: e.chain\*: 2 x HeavyDuty rol e.chain® 5050RHD.12/18/12.300.0

ca. 106 m Travel length: Speed: 4 m/s Acceleration: 0,8 m/s<sup>3</sup>

around 25 kg/m on each Chain Fill weight:

2 e.chainsystems\* to supply the trolley travel. Supply, installation and maintenance by iguse.

### EMO Schiffentlader, Holland

Branche:

2 x HeavyDuty-Rollen e.kette® e.kette\*: 5050RHD.12/18/12.300.0

Verfahrweg: Geschwindigkeit: 4 m/s

Beschleunigung: 0,8 m/s<sup>2</sup> ca. 25 kg/m pro Kette

2 e.kettensysteme® zur Versorgung der Katzfahrt Lieferung, Montage und Wartung durch igus\*.





# Mining industry Bergbau-Industrie



Rotary application on a bucket-wheel excavator using igus<sup>a</sup> e.chainsystem<sup>a</sup> Drehbewegung an einem Schaufelradbagger mit igus" e.kettensystem"

# Brown coal industry Braunkohleindustrie



The bucket is turned by 180° with the help of an iguse e.chainsysteme Der Wagon wird mit Hilfe einer igus° e.kette° um 180° gedreht



### Severoceske doly a.s., Bilina

Mining industry 600.35.300/4650.0 e.chain\*: Travel length: 10 m 0.1 m/s Speed: Acceleration: 0.5 m/s<sup>2</sup> Bucket-Wheel-Reclaimer PV 2400 The e.chain is on the slewing gear

Bergbau Industrie 600.35.300/4650.0 e.kette=: Verfahrweg: Geschwindigkeit: 0,1 m/s

Beschleunigung: 0,5 m/s<sup>2</sup>

Schaufelradbagger PV2400. Die e.kette® befindet sich im Bereich des Drehkranzes.

### CEZ a.s. coal power plant

Power plant e.chain\*: 5050.51.500.0 Travel length: 10 m Speed: 0.25 m/s Acceleration: 0.1 m/s<sup>2</sup>

The e.chain<sup>e</sup> ensures power supply

tipping.

### CEZ a.s. coal power plant

Power Plant e.kette\*: 5050.51.500.0 Verfahrweg: Geschwindigkeit: 0,25 m/s Beschleunigung: 0,1 m/s<sup>3</sup>

Der Wagon wird durch eine 180°-Drehung über dem Kohlebunker entleert. Die e.kette<sup>a</sup> sichert die Energieversorgung der Drehvorrichtung.



# More examples of heavy

# and extreme applications Mehr Beispiele schwerer & extremer Anwendungen



Norway. Vertical boom for Aker Kværner Maritime Hydraulics AS. Specific for the West E-Drill semi-submersible platform. Norwegen. Stehende Anwendung für Aker Kværner Maritime Hydraulics AS. Konfektioniert für die halb-versenkbare Plattform West Edrill.



Czech Republik. Pońci company CEZ a.s. Power supply to transport coal into gung für Kohle-Befund



Germany. Decommissioning research reactor Karlsruhe. A challenging Zig-Zag application has become part of the decommissioning of a nuclear power plant.

Rückbau Forschungsreaktor Karlsruhe. Die Demontage eines Kernkraftwerks mit einer Zick-



Czech Republik. Lhoist a.s. BBP (Building block principle) steel construction for spreader in lime plant. Lhoist a.s. Baukastenprinzip-Stahlkonstruktion in Kalkwerk.

Czech Republik. BBP for coal bulk handling. The e.chain® has cover system. Tschechien. Eingehaustes e.kettensystem® direkt am Kohleförderband.

power plant.



Czech Ventilation system in underground storage in Germany, BASF in Ludwigshafen, preparer for Belüftungsmaschine im fertiliser, since 1998, Untergrundlager eines e.chaine: 4040.32.250.0 \* BASF in Ludwigshafen, Räumer , fül Dungemittel, seit 1998, e.kette

zu walzenden Schienen.



Midland Bricks in Australia is the biggest brick manufacturer in the world! Three e.chains® work 24 hours a day, since 2003, and they look just like the first day. Midland Bricks in Australien ist der größte Ziegelhersteller der Welt! Drei Energieketten sind seit 2003 rund um die Uhr in Betrieb und sehen immer noch aus wie am ersten Tag.



Slovakia, aluminium plant - working for 9 years trouble-free. Travel length is 62 m, travel speed 0,3 m/s. Slovaia, Aluminiumwerk - ameitet seit 9 Jahren fehletfrei Verfahrweg 62 m ka schwin-



Maanshan Steel and Iron Plant in China:

High temperature, heavy load, lots of dust and high speed. Maanshan Stahl- und Eisenwerk: Hohe Temperaturen, große Lasten, viel Staub und hohes Tempo.



Czech Bepublik Ventilation machine in



# More examples of heavy and extreme applications Mehr Beispiele schwerer & extremer Anwendungen



Austria, Niklasdorf, ABV, district heating Österreich, Niklasdorf, ABV, Fernwärmeanlage

Quay side crane travel equipped with igus® e.chainsystems®. Travels up to

Kran Kaifahrt mit igus® e.ketten-

systemen®. Lange Verfahrwege bis

800 m are possible.


800m sind möglich.



RTG in India, Travel: 22 m, e.chain®: 5050.30.550.0, Customer: Kalmar for ATM RTG in Indien, Verfahrweg: 22 m, e.kette®: 5050.30.550.0, Kunde: Kalmar, for ATM



Plaster dust Gipsstaub



Norway: e.chain® with chainflex® in Truck washing facility. Fine road-dust and gravel/mud. igus® chainflex® cables working well.

Norwegen: e.kette® mit chainflex® in einer LKW-Waschanlage. Kommt täglich in Kontakt mit Stra-Benstaub und Schlamm. chainflex®-Kabel arbeiten hervorragend.



China, Shagang Steel and Iron Plant, high temperature, high speed, lots of dust. Shagang Stahl- und Eisen-Werk in China. Hohe Temperaturen, hohe Geschwindigkeiten, viel Staub.



Czech Republik. BBP in CEZ a.s. Power plant supply for dredger excavator in a coal dump Tschechien. CEZ a.s. Baukastensystem zur Energieversorgung eines Kohle-



material stock. Langer Verfahrweg in einem Schütt-



Crane builder Noell in Panama. Application: RTG; Travel: 19,5 m; speed 60 m/min. Kranbauer Noell in Panama, Anwendung: RTG; Verfahrweg: 19,5 m; bis 60 m/min.



Czech Republik. Shipyard Kresice-Loubi; Refueling point for cargo ships. Tschechien. Schiffswerft Kresice-Loubi; Tankstelle für Frachtschiffe.






Meishan Steel and Iron Plant, Nanjing in China, Crane, lots of dust, high speed. Meishan Stahl- und Eisen-

werk, Nanjing in China. Kran, viel Staub, hohes Tempo.



# Strong design Starkes Design

e.chainsystem® E4/4 e.kettensystem® E4/4



KMA, "All-round" mounting potential, pivoting or locking KMA- Anschlusselemente mit "Rundum"- Befestigungsmöglichkeit

Optimized glide surfaces: No sliding shoes, no loose parts Optimierte Gleitflächen: Keine Gleitschuhe, keine losen Teile

Highly secure double lock Doppelter Verschluss hält sicher

Lateral wear allowance Seitliche Verschleiß-

zulage

Openable and removable lid for energy tube

Deckel bei Energierohr schwenkbar und he-High torsion stability through tongue and

Extendable with crossbar and locking clip for large hoses and tubes Erweiterbar mit Bügel

groove design Hohe Torsionssteifigkeit durch

und Rastclip für dicke Schläuche und Rohre Strain relief elements can be integrated in the mounting bracket Zugentlastungselemente

Crossbars removable on both sides, saves time installing and maintaining Stege beid-

seitig herausnehmbar, spart Montagezeit

im Anschlusselement integrierbar



Robust double stop dog system Robustes doppeltes Anschlagsysten

# Long travels: System P4 Lange Wege: System P4 Heavy Duty: Strengthened versions

Heavy Duty: Verstärkte Ausführungen


The tested and proven series 4040 and 5050 now also in Heavy Duty options: 4040HD and 5050HD:

Designed for extremely heavy fill weights at high speeds. Reinforced version of pin\*\* as well as side wall\*.

- Bearing surfaces enlarged four-fold in the range of stops
- Side-wall thickness and bearing surface
- of the pin reinforced for up to 140 % Available with or without rollers
- \* Compared to series 4040 and 5050 \*\* Pin support area compared to series 5050

Die bewährten Serien 4040 und 5050 nun auch verstärkt: 4040HD und 5050HD: Für extrem schwere Zusatzlasten bei hohen Geschwindigkeiten entwickelt. Verstärkte Aus-

- führung des Bolzen\*\* sowie der Seitenwand\*. Tragende Flächen im Bereich der Anschläge 4-fach vergrößert
- Seitenwandstärke, tragende Fläche des Bolzens bis zu 140 % verstärkt
- Mit und ohne Rollen lieferbar \* im Vergleich Serie 4040 und 5050 \*\* tragenden Fläche des Bolzens im Vergleich Serie 5050



5050 HD to classic 5050: Y: +120%, X: +7,5 mm 4040 HD to classic 4040: Y: +140%, X: +9 mm

### More e.chainsystems®

Weitere e.kettensysteme®



System E4.1 - One for all System E4.1 - Eine für Alles



Travel up to 800 m: rol e.chain® Verfahrwege bis 800 m: Rollen e.kette®



Travel more than 800 m: System P4 Verfahrwege mehr als 800 m: System P4

E4.350: Carries heavy loads efficiently and safely - additional load up to 600 kg/m E4.350: Große Lasten effizient und sicher führen – Zusatzlast bis 600 kg/m

# Polymer accessories

# Kunststoff-Zubehör

Polymer and metal accessories

Kunststoff- und Metall-Zubehör



tential, pivoting or locking KMA, "Rundum"-Befestigungsmöglich-



potentials Vielfältige Möglichkeiten zur Innenaufteilung



KMA, "All-round" mounting po- Numerous interior separation Extension link for "endless" ex- Spacer for side-mounted chains tension Mittellasche zur "Endlos"-Verbreiterung



gende Ketten



Extender crossbar for large hoses Erweiterungsbügel für große



tegrated in the mounting element Zugentlastungselemente im An-



Strain relief elements can be in- Mounting bracket pivoting



Available as enclosed, snap-open tube Als geschlossenes, a bares Rohr erhältlich



Floating towning arm, to counter nehmer, zum Ausgleich von Hori-

Führungsrinnen aus Aluminium und Stahl






Heavy-duty assembly kit suitab- Extension link support for e.chain- Clamps for safe cable strain relief le for igus<sup>®</sup> guide trough systems system<sup>®</sup> with several extension Bügelschellen zur sicheren Heavy-Duty-Montageset passend links Mittelbandabstützung für e.kettensysteme® mit Mittelbändern





Easy-to-install easy PPDS 2.0: Electronic monitoring module monitors the push-pull forces of the e.chains® online to prevent damages to the system as well as failures through preventive maintenance



## Facts and tests


# Fakten, Zahlen & Tests

All tested: Numbers and facts

Alles getestet: Zahlen und Fakten



Always more than 80 tests of e.chains® and chainflex® cables running at the igus® testlab. Many igus® e.chainsystems® are certified, tested and awarded. Ask us! Ständig mehr als 80 Tests von e.ketten® und Chainflex®-Leitungen im igus®-Versuchslabor. Viele igus® e.kettensysteme® sind zertifiziert, getestet und prämiert. Fragen Sie uns!



Save space with CF310 single conductors High bending fatigue strength at

- small bending radii
- Optimal height/width ratio, thanks to small bending radii
- Minimal bending radii, even in long. travel applications

Bauraum sparen mit CF310 Einzeladern

- Hohe Biegefestigkeit bei geringen Leitungsradien Durch geringe Radien optimales Ver-
- hältnis Anlagenhöhe zu Anlagenbreite Auch auf langen Wegen niedrigste Biegeradien

8 20.000 2 18.000 16.000 14.000 + 154 % 10.000 8.000 6.000 4,000 2.000

### E4/4: high pull-force resistance

- Long travel distances up to 800 m through high load carrying capacity
- High additional loads on long travels High speeds and accelerations
- E 0,7 0,6 0.5 - 74 % 0.4 0.3 0.2 0,1 0,0

### Low wear for long travel applications

- Low abrasion for glide applications Constantly low wear after short running
- Further minimization by the application
- of roller chains



- Durch hohe Belastbarkeit hohe Verfahrwege bis 800 m
- Hohe Zusatzlasten auf langen Verfahr-
- Hohe Geschwindigkeiten und Beschleunigungen

Geringe Reibung bei langen Verfahrwegen Geringer Abrieb bei gleitenden Anwen-

- dungen Konstant geringe Abnutzung nach
- kurzer Einlaufzeit Weitere Minimierung durch den Einsatz

von Rollenketten

# chainflex® cables chainflex® Leitungen

Space saving and oil resistant: chainflex® cables Platzsparend und ölbeständig: chainflex®-Leitungen

More than 950 chainflex® cables developed especially for the use in e.chainsystems®

- Wear resistant TPE, PUR and oil-resistant PVC outer jackets Halogen-free and/or flame-retardant materials
- Different certificates: UL, CSA, CE, DESINA, CEI Smallest radii up to 4 x d

Uber 950 chainflex®-Leitungen speziell für den Einsatz in e.kettensystemen® entwickelt

 Hoch abriebfeste TPE, PUR und ölfeste PVC Mantelwerkstoffe Halogenfreie und/oder flammwidrige Werkstoffe

12 Fasern - alle Lichtwellenleiter sind über viele Millionen Biegezyklen getestet

IGUS CHAINFLEX® CF310.

- Verschiedene Zulassungen: UL, CSA, CE, DESINA, CEI
- Kleinste Radien bis zu 4 x d
- - Certificates and approvals for igus® chainflex® cables

# **3)** € (€ **(**

### IGUS CHAINFLEX® CFBUS.001 Bus cables: chainflex® bus cables are available for all continuous bus systems within e.chains®. Also in large cross sections, for example 3 x 2 x 2.5 mm² or with power supply cores in the same cable. Busleitungen: chainflex®-Busleitungen sind für alle gängigen Bussysteme für den e.ketten®-Einsatz lieferbar. Auch in "Heavy Duty" Querschnitten von z. B. 3 x 2 x 2,5 mm² oder mit Spannungsversorgungsadem in IGUS CHAINFLEX® CFLG.6G.T

IGUS CHAINFLEX® CF9. Control cables: PVC, PUR, TPE - A wide selection of materials for all applications - also shielded and unshielded cables and a large number

Fibre optic and coaxial cables: Plastic (980/1000) or fibre glass (62.5/125 or 50/125), 1, 2, 6 or 12 fibres – all fibre optic cables are tested for over several million flexing cycles. Lichtwellenleiter und Koax: Kunststoff (980/1000) oder Glasfaser (62,5/125 oder 50/125), 1, 2, 6 oder







Single core CF Crane: Shielded highly flexible single core for up to 6/10kV. Medium voltage cable for the most demanding requirements in crane building, heavy machinery, etc. Cross sections: 1 x 25/16 to 1 x 95/16. Einzelader CF Crane: Geschirmte hochbiegefeste Einzel ader für bis zu 6/10kV. Mittelspannungsleitung für allerhöchste Ansprüche im Kranbau, Schwermaschinen uvm. Querschnitte: 1 x 25/16 bis 1 x 95/16.mm².



### iglidur® and igubal® iglidur® und igubal® 40 lubricant-free materials

40 schmierfreie Werkstoffe



iglidur® - maintenance- and lubricationfree Bearings, made from high-tec polymers - Lifetime predictable


- Maintenance- and lubrication-free
- Corrosion resistance High dirt resistance
- High vibration dampening
- Very low tendency to creep ▶ More Information: www.iglidur.eu

iglidur® - Wartungs- und schmiermittelfreie Gleitlager aus Hochleistungspolymeren - Lebensdauer berechenbar

igubal® maintenance- and lubrication-free

- Wartungs- und schmiermittelfrei
- Korrosionsbeständigkeit Unempfindlich gegen Schmutz
- Hohe Druckfestigkeiten Geringe Reibwerte
- Hohe Verschleißfestigkeit Mehr Informationen: www.iglidur.de

### Self-aligning Spherical Bearings Selbsteinstellende Gelenk- & Stehlager





### e-loop®

### For top drive systems

To guide cables safely in hanging applications, igus® has developed the e-loop® as an alternative to the service loop.

### e-loop® modular energy chain system

3-dimensional applications. result, the cables are kept The e-loop® combines the completely relieved of strain. In order to safely and reliably advantages of a plastic The modular e-chain® made guide cables and hoses in energy chain with those of of high-performance polymer hanging and especially top a high-strength composite always enables a defined drive applications, igus® rope. Inside the chain, the bend radius and easily copes e-loop® rope transfers the pull forces with vibrations and impacts. as an alternative to the to the mounting brackets service loop - ideal for and the structure. As a




Continuous outdoor testing of acompletelyhamessede-loop® with cable filling for a 500t top drive. Result: the test already completed 170.000 double strokes - equivalent to 4.5 years top drive service life.

### e-loop® | Design









### Time saving handling for rig moves

Integrated strain relief for all cables and hoses to install and remove the entire system for rig moves without disconnecting the cable package.

### Available for all top drives

The mounting bracket makes it possible to be installed to any top drive type. Two types of mounting brackets available, either hook (eyelet) or flange style.

### Suitable for all environemts

Thanks to the used materials the e-loop® system is suitable to be used in arctic or desert conditions. It provides great chemical and UV resistance.

### Weather-proof design

One drag chain style loop which fits all service loops/cables (Power, Aux & Control) into **ONE compact** system. It is possible to access, replace and maintain all cables and hoses individually - even in operation.

### Space saving design

The system fits into the smallest mast types due to a very small bend radius of the e-loop®.


### High pulling loads

The composite rope in the center core is 15x stronger than a steel rope and guides all acting forces into the end brackets. Cables are relieved from all strain.







### e-loop® | Product range overview





### e-loop® | Installation dimensions





ELP.430		
4-chamber design interior separation	Standard fastening: hook-type mounting bracket without flange	Special solution: hook-type mounting bracket with flange, optional
Ba ø 430 Bi ø 360		

### chainflex® CFSPECIAL.5xx

Cable package for top drive systems



# The right cable package consisting of motor, data & hybrid cable for your top drive system

For the energy chain e-loop®, a high-quality, modular family of cables is being created that are exactly matched to this application and guarantee maximum durability. With the new CFSPECIAL.5xx cables, there is now finally a suitable range of cables in the chainflex® catalogue, which can save a further 35% in costs when purchased from this single igus® source.

### chainflex® CFSPECIAL.5xx | Product range overview

PUR data cable CFSPECIAL.532

igus" channes" (FSFECIALS)2				
Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFSPECIAL.532.15.08.02	(8x(2x1.5)C)C	30.0	513	1014
CFSPECIAL.532.15.16.02	(16x(2x1.5)C)C	36.5	972	1669

### PUR motor cable CFSPECIAL.572

Part No.				
	Number of cores and conductor nominal cross section	Outer diameter (d) max.	Copper index	Weight
	[mm²]	[mm]	[kg/km]	[kg/km
CFSPECIAL.572.2400.01	(1x240)C	34.5	2581	3081
CFSPECIAL.572.3000.01	(1x300)C	37.5	3189	3799
CFSPECIAL.572.4000.01	(1x400)C	42.0	4269	5007

### PUR motor cable CFSPECIAL.562.PE


sque" chain/flex" (FSPEDNL562FC				
Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFSPECIAL.562.PE.700.01	1G70	19.5	713	867

### PUR hybrid cable (NOV Composite Loop) CFSPECIAL.592

igus" chairfleic D'SPECIALSSS				
Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFSPECIAL.592.001	(30G4.0+4x(2x2.5)C)C	44.0	1,750	2630


Note: The given outer diameters are maximum values and may tend toward lower tolerance limits. G = with green-yellow earth core x = without earth core





# e-loop® Benefits at a glance

- One compact system instead of several service loops, all cables guided in ONE e-loop<sup>®</sup>.
- Less exposed to wind = less swinging inside the mast/derrick = less snags.
- Simple one to one replacement of existing service loop without extensive changings on the rig.
- Small controlled bend radius no fatigue in extreme temperatures & small foot print inside the mast/ derrick.
- Adding or replacing cables possible, even in service.
- Modular system, simple and time-saving maintenance: openable design for quick cable and hose replacement.
- Separate power cables from data cables with 2- or 4-chamber design interior separation.
- Continous flexible power, data & encoder chainflex® cables available.
- Cables visible at all time to prevent unexpected downtimes and simplify maintenance.





# OUR CHEMICALS

**WWW.FISCOSS.TECH** 



# PT FISCO STRATEGIC SYNERGY

### **DRILLING FLUID CHEMICALS**

- Oil Based Mud
- Water based Mud
- Emulsifier
- Fluid Loss Additive
- Commodity Chemicals

### **SPECIALTY CHEMICALS**

- Fluid Separation
- Flow Assurance
- Asset Integrity Assurance
- Oil Spill Tretament

### **ENHANCED OIL RECOVERY (EOR)**

- Alkaline
- Surfactant
- Polymer

### **ADDITIVIES & STIMULATION**

- Fuel Additivies
- Dyes
- Acid Stimulation
- Hydraulic Fracturing

# Drilling and Completion Chemicals Water Based and Oil Based Fluids

Filtration Control Chemicals (Fluid Loss Control Additives)	Carboxy Methyl Cellulose (CMC HV, CMC LV), Poly Anionic Cellulose (PAC R, PAC LV, PAC ULV), Reinated Lignite, Pergelatinized Starch/Drilling strarch High Temperature, Modified Lignite/Organophilic Lignite, Guar Gum, Sodium Polyacrylate (Liquid and Powdered)
Drilling Polymers	Partialy Hydrolyzed Poly Acrylamide (PHPA) Liquid an Powdered, Cloud Point Glycol (Medium and Low), Xanthan Gum, Hydro Ethyl Cellulose (HEC), Sodium Polyacrylate, Synergistic Polymer
Viscosifiers	Bentonite API, Carboxy Methyl Cellulose (CMC), Poly Anionic Cellulose (PAC), Drilling Starch, Guar Gum, Xanthan Gum (XCD Polymer), Drilling Polymer
Shale Stabilizers	PHPA (Powder and Liquid), Polyamine, Synthetic Gilsonite, Sodium Silicate, Sodium Sulphonated Asphalt, Natural Gilsonite, OBM Fluid Loss Reducer
Dispersants/Thinners	Lignited, Lignosulfonated, Tannin, Polyacrylates, Anionic Polymers
Drilling Mud Lubricant and Spotting Fluids	Extreme Pressure Lubricant (Water Based, Esther Based, For Sodium Silicate Mud, Environmentally Friendly Non Toxic Oil Based, Surfactant Based)
Drilling Mud Surfactants and Spotting Fluids, Clean Up Chemicals	Drilling Detergent, Wellbore Cleaner Surfactant Based, Rig Wash, Spotting Fluid (Non Weighted and Weighted)
Loss Circulation Materi	Walnut Shell (Nut Plug) Coarse, Medium, and Fine, Mica Flakes, Blended LCM and Fiberous LCM, Calcium Carbonate F/M/C and Seized Calcium Carbonate, Total Seal F/M/C

# Drilling and Completion Chemicals Water Based and Oil Based Fluids

Emulsifiers for Water Based and Oil Based Systems	Primary Emulsifier, Secondary Emulsifier
Corrosion Inhibitors and Scavengers and Biocides	Corrosion Inhibitor for Oil Line and Gas Line, Acid Corrosion Inhibitor, Oxygen Scavenger, H2S Scavenger, and Biocide
Oil Based Systems and Products	OBM Viscosifier, OBM Filtration Controller, OBM Emulsifiers (Primary and Secondary). OBM Rheology nd Modifier, Organophilic Clay, Organphilic Lignite, Organic Surfactant Emulsifier, OBM Fluid Loss Controller and Amine Treated Lignite, Oil Wetting Agent, Pipe Stuck Additive
Cementing Additivies	Calcium Chloride, Microsilica (Fumed Silica) Gas Block, Silica Flour
Workover and Completion	Calcium Bromide, Zinc Bromide
Commercial Chemicals	Pottasium Chloride (KCL), Pottasium Hydroxide (KOH), Calcium Chloride, Sodium Chloride, Calcium Hydroxide, Pottasium Sulphate, Soda Ash Dense, Sodium Bicarbonate, , Magensium Oxide, Citric Acid

# Oilfield Production Treating and Refinery Chemicals

	T 1 _6 _7 _ 1 _		
	Demulsifier/Desalter		
	Reverse Demulsifier/Deoiler/Water Clarifier		
	Scale Inhibitor (Liquid and Solid Stick)		
	Corrosion Inhibitor (Liquid and Solid Stick)		
	Pour Point Depressant		
	Biocide		
	Anti Fouling Agent		
	Antifoam/Defoamer		
no doute Tours and note on	Oxygen Scavenger		
Production Treating and Refinery	Petroleum Dyes		
Chemicals	Scale Remover		
	Foamer Solid Stick		
	Sulfiding Agent		
	Antioxidant		
	Stabilizers		
	Cetane Improvers		
	Octane Boosters		
	Dewazing Aids		
	Sludge Breakers		
	Demulsifier Component (Concentrate)		
	Pour Point Depressant (PPD Concentrate)		
	Water Clarifier/Deoiler (Cationic Polymer,		
	PAM, Polyether Surfactant, Polydadmac)		
	Imidazolines for Corrosion Inhibitor		
	Triazine H2S Scavenger		
	Phosphonates Antiscalants, Corrosion		
	Inhibitors and Chelating Agents (ATMP,		
	BHMT, HEDP, PBTC, HPAA, EDTA)		
n we hate the ter	Biocide (THPS, Isothiazoline,		
Raw Material Olifield Production	Gluteraldehyde, Benazalkonium Chloride)		
Chemicals	Oxygen Scavenger (Morpholine,		
	Cyclohexylamine, Carbohydrazide,		
	Hydrazine)		
	Linear Alkyl Benzene Sulphonic Acid		
	(LABSA)		
	SUrfacant		
	Monoethanolamine (MEA)		
	Monoethlene Glycol (MEG)		
	Triethyelene Glycol (TEG)		
	Propylene Glycol (PG)		
	Tropyrana diyeor (1 d)		

# **Gas Tretaing Chemicals**

	Antifoam, Sulfolane, Activated Carbon, Activated Alumina,
	Ceramic Ball, Molecular Sieve, Antifouling Agent,
	Purification Adsorbent, Corrosion Inhibitor, H25
Gas Treating	Scavenger, Monoethylene Glycol (MEG), Triethylene Glycol
_	(TEG), Monoethanolamine (MEA), Catalyst (C-Donor and
	D-Donor Catalyst, Chloride Adsorbent, Desulfurizer
	Catalyst, Hydrogenation Catalyst, Arsenic Adsorbent)

# **General Chemicals**

General Chemicals	Ferric Chloride 40%, Caustic Soda Liquid, Caustic Soda Flake, Hydrochloric Acid 32%, Vanadium Pentoxide, Calcium Hypochlorite, Disodium Phosphate, Trisodium Phosphate, Di Iso Propanol Amine, Furfural, Sodium Carbonate (Soda Ash), Sodium Metabisulfite, Citric Acid, Phosphoric Acid, Dimethyl Disulfide (DMDS)
-------------------	--

# WASTE WATER TREATMENT AND MINING TREATMENT CHEMICALS

## **Waste Water Treatment & Boiler Chemicals**

Wastewater Treatment	Coagulants/Flocculants
	Dewatering agents
	Defoamers
	Odor control agents
	Desinfectants

Raw Materials for Water Treatment Chemicals Production	PBTC - HEDP - ATMP - CMIT/MIT - BKC
	Poly Acryic Acid
	Maleic Acid
	Poly Carboxylic Acid
	DBNPA - THPS
	Bronopol

	Oxygen Scavengers
	Corrosion Inhibitor
	Alkalinity Builders
Steam and Hot Water	Scale Inhibitors
Boilers	Antifoam
	Sludge Conditioning Agents
	Condensate Treatment Chemicals
	Cleaning Chemicals

Open Re-circulating Cooling System (Coling Towers)	Corrosion Inhibitor
	Scale Inhibitor
	Biocides & Algaecides
	Antifoams
	Dispersants & Sludge Conditioners
	Cleaning Chemicals

# WASTE WATER TREATMENT AND MINING TREATMENT CHEMICALS

## **Waste Water Treatment & Boiler Chemicals**

Closed Loop	Corrosion & Scale Inhibitors
Recirculating Cooling	Biocides
Systems (Chillers)	Cleaning Chemicals

Reverse Osmosis Plants	Antisclant
	Biocide
	Cleaning Chemicals

Portable & Domestic	Corrosion & Scale Inhibitors
Water Pipe Works	Flocculant & Coagulants

Commodity Chemicals	Odium Flouride
	TCCA Tablet
	Soda Ash Dense
	Phosphoric Acid
	Activated Carbon
	PAC Liquid
	PAC Power

# WASTE WATER TREATMENT AND MINING TREATMENT CHEMICALS

# **Mining Treatment Chemicals**

Maintenance Chemicals	Heavy Duty Cleaner (Degreaser)
	Multi Purpose Cleaner (Degreaser)
	General Cleaner (Degreaser)
	Engine Water Coolant Radiator
	Rust Prevention Control
	Rust Remover
	Polymer Liquid/Wet Polymer
	Polymer Powder/Dry Polymer
Drilling Exploration	Bentonite API 13 A
	PAC LV & PAC R
	Loss Circulation Material
Cool and Dust	Coal Dust Suppressant
Treatment	Road Dust Control
	n∐ Adjuctor
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	pH Adjuster  Floorulant and Congulant
Waste Water	Flocculant and Coagulant
Treatment	Antifoam
	Activated Carbon

### PT FISCO STRATEGIC SYNERGY

### **PRODUCTION: INTEGRITY MANAGEMENT**

- Corrosion inhibitors, specifically formulated and developed for system conditions, transport pipelines, wet gas lines, sub sea flowlines and process applications.
- Biocides for the control and treatment of oilfield bacteria which can lead to microbial induced corrosion, under deposit corrosion and H2S generation.
- H2S scavengers to reduce the H2S content of sour production. Several chemistry types are available and can be used to treat mixed fluid production, gas production or storage vessels.

### **PRODUCTION: SEPARATION MANAGEMENT**

Experienced in the treatment of separation facilities with a range of demulsifiers, deoilers and foam control additives specitically designed for your system. The products are optimally developed on fresh fluids/emulsion in the field locations by our team of separation specialists, and are designed to meet the requirements of the given system. Monitoring services are also available to track the system over time ensuring fluid characteristics are in specification such as BS & W salt content, low residual oil in water levels.

### **PRODUCTION: FLOW ASSURANCE MANAGEMENT**

We offers an extensive range of Flow assurance solutions. We provides a full flow assurance management service. From initial process system evaluation, modelling, and prediction, to freatment design, application, monoring and support work.

The flow Assurance range includes producis for inorganic scale control, wax and asphallene control, pour point. depressants, hydrate prevention, naphthenale control and loamers for aas well deliaulfication.

## PT FISCO STRATEGIC SYNERGY

### WATER INJECTION MANAGEMENT

We supply all your water injection product requirements including oxygen scavengers, primary and secondary biocides, polyelectrolytes, flocculants, coagulants, scale inhibitors and corrosion inhibitors.

### HYDROTESTING, MOTHBALLING & DEWATERING

We developed a full tool box of products for hydrotest, mothball and dewatering operations which includes high performance combination products along with single component biocides, oxygen scavenger and corrosion inhibitors.

### **GAS TREATMENT**

We can supply your needs for gas treatment products, from glycols and amines through to scavengers and antifoams.

### WELL SERVICES: OIL BASED MUD CHEMICALS

Oil-based muds (OBMs) are widely used for drilling operations due to their good fluid loss control, shale inhibition properties and drill-bit lubrication, especially at high temperatures we supply a range of additives for OBMs for differing field conditions. The range includes emulsifier packages which stabilize the internal aqueous phase, develop fluid rheology and prevents fluid loss. Additionally, we supply cleaners, wetting agents, rheology modifiers, fluid loss additives, rheology modifiers and thinners to optimise performance.

### PT FISCO STRATEGIC SYNERGY

### **WELL SERVICES: WELL BORE CLEANERS**

We supply a range of well bore cleaners for the removal of oil based drilling muds from the well bore following drilling operations. The oil based mud cleaners are added at the beginning of well clean up operations and have been developed to:

- Ensure the casing is clean for receiving the completion fluids
- Ensure turbidity & discharge specifications are met
- Reduce clean up times minimizing rig time on site.
- Minimize the environmental impact of the operations

### **WELL SERVICES: ACID STIMULATION**

We supply a range of well stimulation products which can aid increased productivity through use in fracturing and acidizing treatments. We offer hydraulic fracturing and matrix stimulation treatments to restore or enhance well productivity in all types of formations and reservoir environments. We delivers chemicals that address major cementing challenges such as gas migration, loss of circulation, and sustained annulus pressure.

# **OUR CLIENTS**

### PT FISCO STRATEGIC SYNERGY

# SINCE 2017, WE HAVE BEEN WORKING WITH MANY COMPANIES IN INDONESIA

- PT. Pertamina EP
- PT. Pertamina EP CEPU
- PT. Sucofindo Advisory Utama
- PT. Pertamina Hulu Energi
- PT. Sucofindo
- PT. Indosat Tbk
- PT. Tomo and Son
- PT. Prima Multi Cipta Karya
- PT. XL Axiata Tbk
- PT. Mitra Integrasi Informatika
- PT. EJJV Engineering Indonesia
- PT. Global Teknologi Servisindo
- PT. Bima Asri Intermitra
- PT. Surveyor Indonesia (Persero)
- PT. Emp Tonga
- Tately NV
- Job Pertamina-Medco E&P Simenggaris
- PT. Tiarabumi Petroleum
- Repsol Sakakemang B.V
- PT. Samudra Energy Bwpmeruap
- BUT. Pearloil (Sebuku) LTD
- PT.Wahanakarsa Swandiri
- PT. Berca Hardayaperkasa
- PT. Istech Resources Asia
- PT. Geolog Indonesia
- PT. Dunggio Drilling
- PT. Visiontech Indograha
- PT. Intertek Utama Services
- PT. Asta Rekayasa Unggul
- PT. Nusakura Standarindo
- PGN
- Tropik Energy
- Energy Equity

- PT.Depriwangga
- But.Energy Equipty Epic (Sengkang)
- Petrogas (Basin) Ltd
- PT. Chevron Pasific Indonesia
- Chevron Rapak Ltd
- PT. Asry Amanah Timur
- PT. Yokogawa Indonesia
- PT. Devnusa Roga Planindo
- PT. Luas Biru Utama
- PT. Depriwangga Om
- PT. Spektra Megah Semesta
- PT. Tiara Vibrasindo Pratama
- PT. National Oilwell Varco
- PT. Spektra Solusindo
- PT. SPR Langgak
- PT. Biro Klasifikasi Indonesia
- PT. Dahana (Persero)
- PT. Sarana Solusindo Informatika
- PT. Prosys Bangun Persada
- PT. Opac Barata
- PT. Devi Mandiri
- PT. Dowell Anadrill Schlumberger
- PT. Astra Graphia, Tbk
- PT. Accenture
- PT. Crown Worldwide Indonesia
- PT. Bina Sarana Putra
- PT. Sigma Cipta Utama
- PT. Ulima Nitra, Tbk
- PT. Bayu Maritim Berkah
- PT. Solusi Bangun Indonesia, Tbk
- PT. Mesitechmitra Purnabangun
- PT. BKI
- PT. NPU

# **CERTIFICATES**

## PT FISCO STRATEGIC SYNERGY













# CONTACT US



021-27842482



087742900905



info@fiscoss.tech



ITS Tower Lt.9, Jalan Raya Pasar Minggu Nomor 18, Kota Adm. Jakarta Selatan, Provinsi DKI Jakarta, 12510



www.fiscoss.tech